

MSDS FOR BLACK INK:

FOR MODELS - / B001 / C001 / D001

TC10 / 20 / MOZ / 5001 / 6001 / 7001 / 8001 / ZOZ1 / AZ01 / 90Z1 / Y001 / TZ231 / TC50

page 1

Material Safety Data Sheet

Identity		UBO103001		0-174	
SECTION I					
Manufacturer's Name		Emergency Telephone Number			
Fuji Kagakushi Kogyo Company Limited		(06) 471-7071			
Address		Telephone Number for Information			
8-43, Utajima 4-chome, Nishi Yodogawa-ku, Osaka 555, Japan		(06) 471-7071			
		Date Prepared			
		Nov. 1, 1988			
SECTION II - Hazardous Ingredients/Identity Information					
Hazardous Components		CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Paraffin Wax (fume)		8002-74-2	N/A	2.0mg/m ³	N/A
Carbon Black		1333-86-4	3.5mg/m ³	3.5mg/m ³	N/A
Predominant Components		Not Applicable			
Coloring material					
Wax					
Resin					
Additive					
Polyethyleneterephthalate film					
SECTION III - Physical/Chemical Characteristics					
Melting point		N/A	Specific Gravity		N/A
Boiling Point, Evaporation Rate		N/A	Vapor Pressure/Density		N/A
Solubility in Water		No data			
Appearance and Odor		Polyethyleneterephthalate film coated on one side there of with black ink.			

FUJI KAGAKUSHI KOGYO COMPANY LIMITED

TC-10
BLACK RIBBON

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

MSDS FOR BLACK INK:

FOR MODEL - TC-10/20/MOZ/5001/6001/7001/8001
20Z1/A0Z1/90Z1

SECTION IV - Fire and Explosion Hazard Data				
Flash Point	N/A	Flammable Limits	LEL N/A	UEL N/A
Extinguishing Media	Water mist, Foam, Dry powder, CO ₂ gas, others			
Special Fire Fighting Procedures	N/A			
Unusual Fire and Explosion Hazards	None			
SECTION V - Reactivity Data				
Stability	Unstable		Condition to Avoid	
	Stable	X	N/A	
Incompatibility (Material to Avoid)	None			
Hazardous Decomposition or Byproducts	None			
Hazardous Polymerization	May Occur		Condition to Avoid	
	Will Not Occur	X	N/A	
SECTION VI - Health Hazard Data				
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?	
	No	Yes	Yes	
Health Hazards (Acute and Chronic)	No data available			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?	
	No	No	No	
	Ames Test : Negative			
Signs and Symptoms of Exposure	No data available			
Medical Conditions Generally Aggravated by Exposure	No data available			
Emergency and First Aid Procedures	Wash away with soap and water an ink sticking to skin. If ink has contacted eye, wash it with enough water, then consult a doctor.			

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

MSDS FOR BLACK INK:
 FOR MODEL - TC-10/20/MOZ/5001/6001/7001/8001
 20Z1/A0Z1/90Z1

SECTION VI - Precautions for Safe Handling and Use				
Steps to Be Taken in Case Material is Released or Spilled	An inadvertently released or rewound ribbon should be wound again on the reel.			
Waste Disposal Method	No Special			
Precautions to Be Taken in Handling and Storing	Should be stored at dark and cold place. Do not pull the ribbon out of cassette except when mounting it on the printer.			
Other Precautions	None			
SECTION VII - Control Measures				
Respiratory Protection (Specify Type)	None			
Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (General)	N/A	Other	N/A
Protective Gloves	N/A	Eye Protection	N/A	
Other Protective Clothing or Equipment	N/A			
Work/Hygiene Practices	None			

FUJI KAGAKUSHI KOGYO COMPANY LIMITED

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

