

MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Endust Single - 152a Duster w/ Bitterant

PRODUCT DESCRIPTION: HFC 152a Dusting Gas

PRODUCT CODE: 11384

MANUFACTURER

Norazza, Inc.
3938 Broadway
Buffalo NY 14227

Product Stewardship: 716-677-4662

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300

CANUTEC (Canadian Transportation) :(613) 996 - 6666

Emergency Phone :(716) 677-4662

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Flammable liquid and vapor.

POTENTIAL HEALTH EFFECTS

EYES: Avoid contact with eyes; may cause redness, irritation and conjunctivitis.

SKIN: Liquid contact could cause frostbite.

INGESTION: Not likely to be ingested.

INHALATION: Headache, nausea, and possible coordination problems. High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Symptoms of overexposure include: stinging, tearing, redness and pain.

SKIN: Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold" burn).

INGESTION: Not a likely route of exposure.

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS depression and cardiac arrhythmia may result.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

CARCINOGENICITY: NOT listed

MUTAGENICITY: Not Established



MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

Chemical Name	Wt.%	CAS	EINECS
1,1-difluoroethane (HFC-152a)	> 99.9	75-37-6	
Ethanol	< 1	64-17-5	200-578-6
Denatonium benzoate	< 0.0001	37343-36-6	

4. FIRST AID MEASURES

EYES: Flush eye with water for 15 minutes. Get medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: < -50°C (-58°F)

FLAMMABLE LIMITS: 3.9 to 16.9

AUTOIGNITION TEMPERATURE: 154°C (849°F)

GENERAL HAZARD: Aerosol cans may erupt with force at temperatures above 120F.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Carbon dioxide, carbon monoxide, fluorine, hydrofluoric acid, carbonyl halides.

EXPLOSION HAZARDS: Vapors, when present in the flammable range (listed above), especially in a confined or poorly ventilated space, can be ignited with a flame or high intensity source of heat.

FIRE FIGHTING PROCEDURES: Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH approved or equivalent) and full protective gear.



MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

RELEASE NOTES: Spills and releases may have to be reported to Federal and/or local authorities.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Contents may be under pressure. Exercise caution when opening container. If containers have been stored in direct sunlight or heated above the boiling point of the solvent, the container should be cooled to below the boiling point before opening.

HANDLING: Use with sufficient ventilation to keep employee exposure below recommended limits. Provide adequate ventilation for storage, handling and use, especially for enclosed or low spaces. Avoid contact of liquid with eyes and prolonged skin exposure. Do not allow product to contact open flame or electrical heating elements because dangerous decomposition products may form.

STORAGE: Keep away from sources of ignition.

STORAGE TEMPERATURE: Contents under pressure. Do not expose to heat or store above (120) F (49) C.

STORAGE PRESSURE: Store at local atmospheric pressure.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		Supplier OEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
Ethanol	TWA	1000 ppm	1900 mg/m ³	1000 ppm	1880 mg/m ³	NL	NL
	STEL	NL ppm	NL mg/m ³	NL ppm	NL mg/m ³	NL	NL
Denatonium benzoate	TWA	[1]	[1]	[1]	[1]		
OSHA TABLE COMMENTS:							
1. NOT ESTABLISHED							

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

WORK HYGIENIC PRACTICES: Wash hands before eating and wash before reuse.

OTHER USE PRECAUTIONS: Emergency shower and eyewash facility should be in close proximity.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Gas

ODOR: Low odor.

COLOR: Colorless

PERCENT VOLATILE: 99.9+

VAPOR PRESSURE: 87 psia at 25°C

VAPOR DENSITY: 2.4 (Air=1)

BOILING POINT: -25°C (-13°F)

FLASHPOINT AND METHOD: < -50°C (-58°F)

SOLUBILITY IN WATER: 0.28 wt% @ 25C

SPECIFIC GRAVITY: 0.910

(VOC): < 1.000 % by weight

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: Heat, flames, ignition sources, and incompatibles.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, fluorine, hydrofluoric acid, carbonyl halides.

INCOMPATIBLE MATERIALS: Incompatible with alkali or alkaline earth metals - powdered Al, Zn, Be,



MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

Chemical Name	NTP Status	IARC Status	OSHA Status
Ethanol	NOT LISTED	NOT LISTED	NOT LISTED

IARC: NOT listed**NTP:** NOT listed**OSHA:** NOT listed**NEUROTOXICITY:** Exposure to high concentrations may effect the nervous system.**REPRODUCTIVE EFFECTS:** Not Established**TERATOGENIC EFFECTS:** NOT listed**MUTAGENICITY:** Not Established

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: There is limited information available on the environmental fate and effects of this material. The primary environmental concern for release is the impact on aquatic and terrestrial species. Due care should be taken to avoid the accidental release of this material into the environment.

ECOTOXICOLOGICAL INFORMATION: Not Established

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

GENERAL COMMENTS: Dispose of in a manner consistent with federal, state, and local regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)**PROPER SHIPPING NAME:** 1,1-difluoroethane**PRIMARY HAZARD CLASS/DIVISION:** 2.1**UN/NA NUMBER:** 1030**PACKING GROUP:** NA

MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008

MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant**PACKING GROUP:** NA**NOTE:** Cargo aircraft ONLY. Copy of DOT-E 11516 must be presented.**VESSEL (IMO/IMDG)****SHIPPING NAME:** 1,1-difluoroethane**UN/NA NUMBER:** UN1030**PRIMARY HAZARD CLASS/DIVISION:** 2.1**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****FIRE:** Yes **PRESSURE GENERATING:** Yes **ACUTE:** Yes**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)****CERCLA REGULATORY:** Listed in table 302.4 of 40CFR Part 302 as a hazardous substance with a reportable quantity. Releases to air, land, or water which exceed the RQ must be reported to the national response center.**CERCLA RQ:** 100 lbs.**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
1,1-difluoroethane (HFC-152a)	75-37-6
Ethanol	64-17-5

TSCA REGULATORY: This product is listed on the TSCA Inventory.**OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)****29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS****CHEMICALS:** None of the chemicals in this product are considered highly hazardous by OSHA.**CALIFORNIA PROPOSITION 65:** This product does not contain any chemicals known to the State of California to cause cancer.**RCRA STATUS:** D001**OSHA HAZARD COMM. RULE:** Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.**CANADA**


MATERIAL SAFETY DATA SHEET

Date Issued: 12/04/2008
MSDS No: 11384

Endust Single - 152a Duster w/ Bitterant

REVISION SUMMARY: New MSDS

NFPA CODES



DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

