

MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Endust Duster w/ Bitterant

PRODUCT CODE: 246-050/248-050/255-050

ACTIVE INGREDIENT(S): 1,1,1,2-Tetrafluoroethane

MANUFACTURER

Norazza, Inc.
3938 Broadway
Buffalo NY 14227

Product Stewardship: 716-677-4662

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation) :(800) 424 - 9300
CANUTEC (Canadian Transportation) :(613) 996 - 6666
Emergency Phone :(716) 677-4662

2. HAZARDS IDENTIFICATION

HAZARD DESIGNATION

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Clear, Colorless, Volatile Liquid

IMMEDIATE CONCERNS: Warning! High concentrations of vapor can reduce oxygen available for breathing. Harmful if inhaled. May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products.

POTENTIAL HEALTH EFFECTS

EYES: Liquid contact can cause irritation, which may be severe.

SKIN: Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION: High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and possibly death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Can cause severe eye irritation.

SKIN: Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold" burn).

INHALATION: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ACUTE TOXICITY: Overexposure may cause dizziness and loss of concentration. At higher levels, CNS



MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

Chemical Name	Wt. %	CAS	EINECS
1,1,1,2-Tetrafluoroethane	> 99	811-97-2	212-337-0
Ethanol	< 1	64-17-5	200-578-6
Denatonium benzoate	< 0.0001	37343-36-6	

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: In case of cold burns (frostbite) caused by rapidly expanding gas or vaporizing liquids, get medical attention promptly.

INGESTION: Ingestion is unlikely because of the physical properties and is not expected to be hazardous. Do not induce vomiting unless instructed to do so by a physician.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: Because of the possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used with special caution and only in situations of emergency life support. Treatment of overexposure should be directed at the control of symptoms and the clinical conditions.

5. FIRE FIGHTING MEASURES

FLASHPOINT AND METHOD: Not Applicable

FLAMMABLE LIMITS: None*

AUTOIGNITION TEMPERATURE: > 750°C (1382°F)

FLAMMABLE CLASS: Not Applicable

FLAME PROPAGATION OR BURNING RATE OF SOLIDS: Not Applicable

EXTINGUISHING MEDIA: As appropriate for combustibles in area.

EXPLOSION HAZARDS: This product is not flammable at ambient temperatures and atmospheric pressure. However, this material may become combustible when mixed with air under pressure and exposed to strong ignition sources.



MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

GENERAL PROCEDURES: Isolate hazard area. Keep unnecessary and unprotected personnel from entering.

RELEASE NOTES: Spills and releases may have to be reported to Federal and/or local authorities.

7. HANDLING AND STORAGE

HANDLING: Follow standard safety precautions for handling and use of compressed gas cylinders.

STORAGE: Store in a cool place in original container and protect from sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL		ACGIH TLV		SupplierOEL	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1,1,1,2-Tetrafluoroethane	TWA	NE		NE		1,000 ppm [1]	[1]
Ethanol	TWA	1000 ppm	1900 mg/m ³	1000 ppm	1880 mg/m ³	NL	NL
	STEL	NL ppm	NL mg/m ³	NL ppm	NL mg/m ³	NL	NL
Denatonium benzoate	TWA	[2]	[2]	[2]	[2]		

OSHA TABLE COMMENTS:

- * (AEL)=Acceptable Exposure Limit as established by the manufacture
- NOT ESTABLISHED

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN: Skin contact with liquid may cause frostbite. General work clothing and gloves (leather) should

MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

Chemical Name	Boiling Point (°C)	Freezing Point (°C)	Solubility in Water	Specific Gravity
1,1,1,2-Tetrafluoroethane	-26.4	-101	NEGLIGIBLE	1.21

PHYSICAL STATE: Gas**ODOR:** Faint ethereal odor**pH:** Neutral**PERCENT VOLATILE:** 99.99+ at 20°C (68°F)**VAPOR PRESSURE:** 85.8 psi at 21.1°C (70°F)**VAPOR DENSITY:** 3.5 (Air=1)**BOILING POINT:** -26.2°C (-15.1°F)**FREEZING POINT:** -101°C (-149.8°F)**FLASHPOINT AND METHOD:** Not Applicable**SOLUBILITY IN WATER:** Negligible**EVAPORATION RATE:** > 1 (CCL4=1)**SPECIFIC GRAVITY:** 1.220 (water=1) at 20°C (68°F)**(VOC):** < 1.000 % by weight

10. STABILITY AND REACTIVITY

STABLE: Yes**HAZARDOUS POLYMERIZATION:** No**STABILITY:** Stable.**POLYMERIZATION:** Will not occur.**CONDITIONS TO AVOID:** Stable. However, may decompose if heated.**HAZARDOUS DECOMPOSITION PRODUCTS:** When exposed to high temperatures or flames this

MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

Chemical Name	INHALATION LC ₅₀ (rat)
1,1,1,2-Tetrafluoroethane	> 500000 ppm

INHALATION LC₅₀: > 500000 ppm, 4-hour

CHRONIC: Chronic NOEL - 10,000 ppm

SUBCHRONIC: Subchronic inhalation (rat) NOEL - 50,000 ppm

CARCINOGENICITY

Chemical Name	NTP Status	IARC Status	OSHA Status
1,1,1,2-Tetrafluoroethane	NOT LISTED	NOT LISTED	NOT LISTED
Ethanol	NOT LISTED	NOT LISTED	NOT LISTED

SENSITIZATION: Cardiac sensitization threshold (dog) 80,000 ppm. NOEL - 50,000 ppm.

TERATOGENIC EFFECTS: NOEL (rat and rabbit) - 40,000 ppm.

MUTAGENICITY: Collective data indicate non-mutagenic.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: Degradability (BOD): This material is a gas at room temperature; therefore, it is unlikely to remain in water.

DISTRIBUTION: Octanol Water Partition Coefficient: Log P=1.06

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Federal, State, and Local laws governing disposal of materials can differ. Ensure compliance with proper authorities before disposal.

GENERAL COMMENTS: 1,1,1,2-tetrafluoroethane is subject to U.S. Environmental Protection Agency Clean Air Act Regulations, Section 608 in 40 CFR Part 82 regarding refrigerant recycling.



MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

PACKING GROUP: NA

NAERG: #12

OTHER SHIPPING INFORMATION: Must have a copy of the DOT-SP-10232 with each shipment.

SPECIAL SHIPPING NOTES: Domestic Shipments Only. For International shipments use 1,1,1,2-Tetrafluoroethane, UN3159, 2.2; Pkg. Instr. 200.; Authorization: DOT-SP 10232.; **NOTE:** Copy of the Exemption is required with all shipments.; HAZARD LABEL: Non-Flammable Gas.; ["LTD QTY of class 2" when <120mL (5 oz)]

ROAD AND RAIL (ADR/RID)

KEMLER NUMBER: UN3159

HAZARD CLASS: 2.2

AIR (ICAO/IATA)

SHIPPING NAME: CONSUMER COMMODITY, ORM-D-AIR, DOT-SP 10232

UN/NA NUMBER: ID8000

PRIMARY HAZARD CLASS/DIVISION: 9

PACKING GROUP: NA

VESSEL (IMO/IMDG)

SHIPPING NAME: CONSUMER COMMODITY, ORM-D, DOT-SP 10232

UN/NA NUMBER: ID8000

PRIMARY HAZARD CLASS/DIVISION: 9

PACKING GROUP: NA

LIMITED QUANTITY: 120 mL

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: IMMEDIATE / PRESSURE

PRESSURE GENERATING: Yes **ACUTE:** Yes

313 REPORTABLE INGREDIENTS: Not considered a SARA 313 "Toxic Chemical".

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)



MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

TSCA REGULATORY: This product is listed on the TSCA Inventory.

CLEAN AIR ACT

Chemical Name	Wt. %	CAS
1,1,1,2-Tetrafluoroethane	> 99	811-97-2

CANADA

WHMIS CLASS: Class A, Class D2B.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components of this product are listed on the Canadian DSL.

EUROPEAN COMMUNITY

EEC LABEL SYMBOL AND CLASSIFICATION

Currently not classified according to EEC Directives.

GENERAL COMMENTS: 1,1,1,2-tetrafluoroethane is subject to U.S. Environmental Agency Clean Air Act Regulations, (40CFR Part 82).

COMMENTS WARNING: Contains 1,1,1,2-tetrafluoroethane (HFC-134a), a greenhouse gas which may contribute to global warming.

16. OTHER INFORMATION


APPROVED BY: Pierce A. Pillon **TITLE:** Chemist

REVISION SUMMARY: Revision #: 2. This MSDS replaces the July 02, 2008 MSDS., Any changes in information are as follows: In Section 1: 24 Hour Emergency Phone Numbers In Section 16: Manufacturer Disclaimer

HMIS RATING

HEALTH:	1
FLAMMABILITY:	1
PHYSICAL HAZARD:	0

NFPA CODES



MATERIAL SAFETY DATA SHEET

Date Issued: 03/17/2008

MSDS No: 246-050/248-050/255-050

Date Revised: 08/12/2008

Revision No: 2

Endust Duster w/ Bitterant

DATA SOURCES: Code of Federal Regulations (CFR) The Sigma-Aldrich Library of Regulatory and Safety Data OSHA Hazard Communication Standard (29CFR1910.1200) Various Federal, State and Local Regulations

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

