OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

Material Safety Data Sheet

May be used to comply with OSHA'S Hazard Communication Standard 29 CFR 2910.1200. Standard must be consulted for specific requirements.

U.S. DEPARTMENT OF LABOR

Occupational Safety and Health (Non-Mandatory Form) Form Approved OMB No. 1218-0072

Identity (As Used on Label and List) #202 Big D Fire D	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.					
Section I						
Manufacturer's Name Big D Industries, Inc.	Emergency Telephone Number (800) 535-5053 (800) 654-4752					
Address (number, Street, City, State, and ZIP Code) 5620 S. W. 29th Street (73179)	Telephone Number for Information (800) 654-4752 (405) 682-2541					
P. O. Box 82219	Date Prepared	Date Prepared 01/01/2005				
Oklahoma City, OK 73148	Signature of Prepar	Signature of Preparer (optional)				
Section II - HMIS Rating						
Health 1 Flammability	4	Reactivity	1			
Section III - Hazardous Ingredier	nts/Identity Inform	nation				
Hazardous Components (Specific Chemical Ide	entity: Common Name(s)	OSHA PEL	ACGIH TLV	Other L	imits	
%(optional)				Remnd	i.	
Acetone CAS #67-64-1		500 ppm	500 ppm	-		
Amyl Acetate CAS #628-63-7		100 ppm	100 ppm	-		
Ethyl Acetate CAS #141-78-6	400 ppm 400 ppm					
Liq. Petrole\um Gas - CAS #68476-85-7		1000 ppm	1000 ppm			
Section IV - Physical/Chemical C	haracteristics					
ing Point -44 - 135°F Conc.		Specific Gravity ($H_2O = 1$) 0.5677		N/E		
Boning Form					N/A	
Vapor Pressure (mm Hg.)	N/E	Melting Point			N/A	
	N/E >1	Melting Point Evaporation Rate			N/A <1	
Vapor Pressure (mm Hg.)						
Vapor Pressure (mm Hg.) Vapor Density (AIR = 1) Solubility in Water: Slight		Evaporation Rate				
Vapor Pressure (mm Hg.) Vapor Density (AIR = 1) Solubility in Water: Slight Appearance and Odor: Produces fine mist with	>1 n pleasant fragrance. Liq	Evaporation Rate				
Vapor Pressure (mm Hg.) Vapor Density (AIR = 1) Solubility in Water: Slight Appearance and Odor: Produces fine mist with Section V - Fire and Explosion Ha	>1 n pleasant fragrance. Liq azard Data	Evaporation Rate	N/A			UEL 12.8
Vapor Pressure (mm Hg.) Vapor Density (AIR = 1) Solubility in Water: Slight Appearance and Odor: Produces fine mist with Section V - Fire and Explosion Ha Flash Point (Method Used)	>1 n pleasant fragrance. Liq azard Data	Evaporation Rate	N/A		<1 LEL	

Section VI -	Reactivity Data					
Stability	Unstable		Conditions to Avoid: None			
	Stable	X				
Incompatibility (Ma	aterials to Avoid): Avoid	l contact w	vith strong oxidizing agents such as nitric acid.			
Hazardous Decompo	osition or Byproducts: N	one				
Hazardous Polymerization	May Occur		Conditions to Avoid: None			
	Will Not Occur	X				
Section VII -	· Health Hazard D	ata				
Route(s) of Entry:	Inhalation? Yes	Skin	? Yes Ingestion? Yes			
Health Hazards (Act	ute and Chronic):					
Acute - Propellan	t is an asphyxiant and ma	y exhibit _l	properties at high concentrate. Chronic - Unconsc	ciousness		
Carcinogenicity:	NTP? No	IARO	C Monographs? No OSHA Re	gulated? No		
Signs and Symptom	s of Exposure: Skin - po	ssible fro	stbite burn. Eyes - burning sensation. Inhalation	- Headache, nausea, disorientation.		
Medical Conditions Generally Aggravate		ysema				
Emergency and Firs attn.	at Aid Procedures: Eye conta	act: flush	with large amounts of water. May cause corneal of	damage on prolonged contact. Seek medical		
	give anything by mouth ton if not breathing. Seek		nscious person. Seek Medical attn. Inhalation: rettn.	move person to fresh air . Administer		
Section VIII	- Precautions for	Safe Ha	andling and Use			
Steps to be Taken in	n Case Material is Released o	r Spilled:				
If container is rup	tured and begins to leak,	place in a	well ventilated area and eliminate all ignition sou	irces.		
Waste Disposal Met	thod: do not discard empty	containe	in incinerator or fire. Dispose of in accordance	with Local, State, and Federal regulations.		
Precautions to be Ta	aken in Handling and Storing	: Store in	cool area away from heat or open flame. Do not	store above 130°F as containers may burst		
releasing the high	ly flammable propellant.	"Store as	Level Aerosol (NFPA 30B)			
_	In case of rupture, ventile must not be modified in	_	ent concentrations from reaching flammable leve	els. Note: any copies or redistribution of		
Section IX -	Control Measures					
Respiratory Protection	on (Specify Type): Self	contained	breathing apparatus.			
Ventilation			Local Exhaust:: Doors & windows open	Special N/A		
			Mechanical (General) Fan	Other N/A		
Protective Gloves: I	Rubber or plastic for prolo	onged con	Eye Protection: Safety goggles for splash p	protection		
Other Protective Clo	othing or Equipment: Eye	wash/sho	wer facility nearby			
Work/Hygienic Prac	ctices: Good housekee	ning pract	ces. Avoid skin/eye contact.			

Work/Hygienic Practices: Good housekeeping practices. Avoid skin/eye contact.

N.A. = Not Applicable

N.D. - Not Determined

Page 2

N/E - Not Established

OSHA 174, Sept. 1985