

MSDS FOR RED INK:
FOR MODEL - TC-11/21/30/40

page 1

Material Safety Data Sheet

Identity		UBO 193001		0-176
SECTION I				
Manufacturer's Name		Emergency Telephone Number		
Fuji Kagakushi Kogyo Company Limited		(06) 471-7071		
Address		Telephone Number for Information		
8-43, Utajima 4-chome; Nishi Yodogawa-ku, Osaka 555, Japan		(06) 471-7071		
		Date Prepared		
		Nov. 21, 1988		
SECTION II - Hazardous Ingredients/Identity Information				
Hazardous Components	CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Paraffin Wax (fume)	8002-74-2	N/A	2 mg/m ³	N/A
Predominant Components	Not Applicable			
Coloring material				
Wax				
Resin				
Additive				
Polyethyleneterephthalate film				
SECTION III - Physical/Chemical Characteristics				
Melting point	N/A	Specific Gravity	N/A	
Boiling Point, Evaporation Rate	N/A	Vapor Pressure/Density	N/A	
Solubility in Water	No data			
Appearance and Odor	Polyethyleneterephthalate film coated on one side there of with blue ink.			

FUJI KAGAKUSHI KOGYO COMPANY LIMITED

SECTION IV - Fire and Explosion Hazard Data			
Flash Point	N/A	Flammable Limits	LEL N/A UEL N/A
Extinguishing Media	Water mist, Foam, Dry powder, CO ₂ gas, others		
Special Fire Fighting Procedures	N/A		
Unusual Fire and Explosion Hazards	None		
SECTION V - Reactivity Data			
Stability	Unstable		Condition to Avoid N/A
	Stable	X	
Incompatibility (Material to Avoid)	None		
Hazardous Decomposition or Byproducts	None		
Hazardous Polymerization	May Occur		Condition to Avoid N/A
	Will Not Occur	X	
SECTION VI - Health Hazard Data			
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	No	Yes	Yes
Health Hazards (Acute and Chronic)	No data available		
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No
Signs and Symptoms of Exposure	No data available		
Medical Conditions	Generally Aggravated by Exposure		
	No data available		
Emergency and First Aid Procedures	Wash away with soap and water an ink sticking to skin. If ink has contacted eye, wash it with enough water, then consult a doctor.		

MSDS FOR RED INK:
FOR MODEL - TC-11/21/30/40

page 3

SECTION VI - Precautions for Safe Handling and Use			
Steps to Be Taken in Case Material is Released or Spilled			
An inadvertently released or rewound ribbon should be wound again on the reel.			
Waste Disposal Method			
No Special			
Precautions to Be Taken in Handling and Storing			
Should be stored at dark and cold place. Do not pull the ribbon out of cassette except when mounting it on the printer.			
Other Precautions			
None			
SECTION VII - Control Measures			
Respiratory Protection (Specify Type)		None	
Ventilation	Local Exhaust	N/A	Special N/A
	Mechanical (General)	N/A	Other N/A
Protective Gloves		Eye Protection	
N/A		N/A	
Other Protective Clothing or Equipment			
N/A			
Work/Hygienic Practices			
None			

FUJI KAGAKUSHI KOGYO COMPANY LIMITED

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

