

**IDENTITY (As Used on Label and List)**

**Prang Tempera Paint  
 Ready To Use**

NOTE: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that

**SECTION I**

<b>Manufacturer's Name</b> DIXON TICONDEROGA	<b>Emergency Telephone Number</b> (419) 625-9545
<b>Address (Number, Street, City, State, and ZIP)</b>  1706 HAYES AVENUE SANDUSKY, OHIO 44870	<b>Telephone Number for Information</b> (419) 625-9545
	<b>Date Prepared</b> 05/25/00
	<b>Signature of Preparer (optional)</b>

**SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

<b>Hazardous Components</b> (Specific Chemical Identity; Common Name(s))	<b>OSHA PEL</b>	<b>ACGIH TLV</b>	<b>Other Limits Recommended</b>	<b>%Optional</b>
---	-----------------	------------------	---------------------------------	------------------

Products bearing the CP Certified Products or AP Approved Products seals of the Art and Creative Materials Institute, Inc. are certified in a program of Toxicological evaluation by a Medical expert, subject to review by the Institute's Toxicological Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans or cause acute or chronic health problems.

CONFORMS TO ASTM-4236

**SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS**

<b>Boiling Point</b> N/A	<b>Specific Gravity (H2O = 1)</b> Greater than 1.0
<b>Vapor Pressure (mm Hg)</b> N/A	<b>Melting Point</b> N/A
<b>Vapor Density (Air=1)</b> N/A	<b>Evaporation Rate (Butyl Acetate = 1)</b> N/A
<b>Solubility In Water</b> Nil	
<b>Appearance and Odor</b> Colored liquid, nearly odorless	

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point (Method Used)</b> N/A	<b>Flammable Limits</b> N/A	<b>LEL</b> N/A	<b>UEL</b> N/A
<b>Extinguishing Media</b> Water Spray, Foam, CO2			

**Special Fire Fighting Procedures**  
 Containers may be subject to ignition by fire and may release toxic or other irritating gases

**Unusual Fire and Explosion Hazards**  
 A self contained breathing apparatus should be used for this exposure.

**(Reproduce Locally)**

OSHA 174, SEPT. 1985

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.



OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

**SECTION V - REACTIVITY DATA**

Stability	Unstable	Conditions To Avoid	NONE
	Stable		
Incompatibility (Materials To Avoid)			
NONE			
Hazardous Decomposition or Byproducts			
As with all burning organic matter, Carbon Monoxide and other toxic fumes may be given off.			
Hazardous Polymerization	May Occur	Conditions To Avoid	NONE
	Will Not Occur		

**SECTION VI - HEALTH HAZARD DATA**

Route(s) Of Entry:	Inhalation?	Skin?	Ingestion?
	NO	YES	YES
Health Hazards (Acute and Chronic)			
Conforms to ASTM D-4236			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	N/A	N/A	N/A
Signs and Symptoms of Exposure			
N/A			
Medical Conditions Generally Aggravated by Exposure			
N/A			
Emergency and First Aid Procedures			
Eyes--flush with copious amounts of water and contact a physician Contact with skin--Wash area with soap and water; Ingestion--seek medical attention;			

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to Be Taken in Case Material Is Released or Spilled	Contain and place in approved containers.
Waste Disposal Method	Dispose of per all Local, State, and Federal Regulations.
Precautions to Be Taken in Handling and Storing	Do not store near heat or open flame.
Other Precautions	None

**SECTION VIII - CONTROL MEASURES**

Respiratory Protection (specify Type)			
N/A			
Ventilation	Local Exhaust	Special	N/A
	Mechanical (General)	Other	N/A
Protective Gloves	N/A	Eye Protection	YES
Other Protective Clothing or Equipment			
N/A			
Work/Hygenic Practices			
Contents will stain most fabrics, use of smocks, gloves, etc to protect personel clothing is suggested. Wash hands and surfaces after use.			

