

SKUs covered:

DLT-W2000BLK
DLT-W3700BLK
DLT-W3700WHT
DLT-W1400BLK
DLT-W1300BLK
DLT-W2030BLK
DLT-12044118-028
DLT-12044118-087
DLT-W4400
DLT-09-015108-130
DLT-W2050BLK
DLT-12036001-028
DLT-09-029228-130
DLT-12070119-028
DLT-12070119-087
DLT-W4590
DLT-W9103

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

Madalyn Lane-Redini
Import Analyst
United Worldwide Limited
United Stationers Supply Co.
(847) 699-5000 ext. 2959
FAX: (847) 699-9493
mlane-redini@ussco.com

Material Safety Data Sheet

U.S. Department Of Labor

May be used to comply with

Occupational Safety and Health Administration

OSHA's Hazard Communication Standard,

(Non-Mandatory Form)

29 CFR 1910.1200. Standard must be

Form Approved

consulted for specific requirements.

OMB No. 1218-0072

IDENTITY:

Solid paint (ITEM NO: 09-015108-130、09-029228-130、09090162-028、W1000BLK、W1300BLK、W1400BLK、

Chinese name: 熱固性粉末 W1575、W2000BLK、W2030BLK、W2050BLK、W3700BLK、W3700WHT、W4400、
12044118-028、12044118-087、12037001-028、12014107-028、12036001-028、
12051492-087、W4590、W9103、12070119-028、12070119-087、11289000、11292000)

Note: Blank Spaces are not permitted. If any item is not applicable, or no

(As Used on Label and List)

information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name:

Emergency Telephone Number: 0755-27938666

Jiadianbao Electrical Products (Shenzhen)Co.,Ltd.

Telephone Number for Information: 0755-27938666

Address (Number, Street City, State, and ZIP Code):

Date Prepared: 11-15-04

(Region No. 117)Feng Huang Gang Village, Xin An, Baoan
County, Shenzhen City, Guangdong Province, China

Signature of Preparer(optional): Andy Shum

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Nonylphenol and ethoxylates				0.001
Bisphenol A				0.001-0.002
Lead and organic lead compounds				0.002
Hexavalent Chromium compounds				0.001-0.002

Section III – Physical/Chemical Characteristics

Boiling Point: 745°C

Specific Gravity (H2O=1): 1.2

Vapor Pressure (mm Hg.):

Melting Point: 265°C

Vapor Density (AIR = 1):

Evaporation Rate:

(Butyl Acetate = 1)

Solubility in Water: 0.8%

Appearance and Odor: Liquid, Fragrant Odor

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used):

Flammable Limits:

LEL:

UEL:

Extinguishing Media: the fire extinguisher of CO2 or the other chemistry powder.

Special fire fighting Procedures: 1. The present worker bring the nearest fire extinguisher to extinguish fire.

2. The fire department of our company arrived the fire locale to extinguish fire.

3. Ask the fire company of the local government to helping.

Unusual Fire and Explosion Hazards: None

Section V – Reactivity Data

Stability Unstable Conditions to Avoid

Stable

Incompatibility (Materials to Avoid):

Hazardous Decomposition or Byproducts:

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.



May be used to comply with

Occupational Safety and Health Administration

OSHA's Hazard Communication Standard,

(Non-Mandatory Form)

29 CFR 1910.1200. Standard must be

Form Approved

consulted for specific requirements.

OMB No. 1218-0072

IDENTITY:

Plastic paint (ITEM NO : 09-015108-130 · 09-029228-130 · 09090162-028 · W1000BLK · W1300BLK ·
 W1400BLK · W1575 · W2000BLK · W2030BLK · W2050BLK · W3700BLK · W3700WHT ·
 Chinese name: W4400 · 12044118-028 · 12044118-087 · 12037001-028 · 12014107-028 · 12036001-028 ·
 塑膠油漆 12051492-087 · W4590 · W9103 · 12070119-028 · 12070119-087 · 11289000 · 11292000)

Note: Blank Spaces are not permitted. If any item is not applicable, or no

(As Used on Label and List)

information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name: Jiadianbao Electrical Products (Shenzhen)Co.,Ltd. Emergency Telephone Number: 0755-27938666
 Telephone Number for Information: 0755-27938666
 Address (Number, Street City, State, and ZIP Code): (Region No. 117)Feng Huang Gang Village, Xin An, Baoan Date Prepared: 11-15-04
 County, Shenzhen City, Guangdong Province, China Signature of Preparer(optional): Andy Shum

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Polyaromatic Hydrocarbons				0.003
Nonylphenol and ethoxylates				0.001
Hexavalent Chromium compounds				0.001–0.002

Section III – Physical/Chemical Characteristics

Boiling Point: 113°C Specific Gravity (H₂O=1): 0.86
 Vapor Pressure (mm Hg.): Melting Point: -81°C
 Vapor Density (AIR = 1): 0.81 Evaporation Rate:
 (Butyl Acetate = 1)
 Solubility in Water: 0.5%
 Appearance and Odor: Liquid, Fragrant Odor

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used): 165°C Flammable Limits: LEL: UEL:
 Extinguishing Media: the fire extinguisher of CO₂ or the other chemistry powder.
 Special fire fighting Procedures: 1. The present worker bring the nearest fire extinguisher to extinguish fire.
 2. The fire department of our company arrived the fire locale to extinguish fire.
 3. Ask the fire company of the local government to helping.
 Unusual Fire and Explosion Hazards: None

Section V – Reactivity Data

Stability Unstable Conditions to Avoid
 Stable
 Incompatibility (Materials to Avoid):
 Hazardous Decomposition or Byproducts:
 Hazardous May Occur Conditions to Avoid: make fire far away.

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department Of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY:

Metal paint (ITEM NO : 09-015108-130 · 09-029228-130 · 09090162-028 · W1000BLK · W1300BLK · W1400BLK ·
Chinese name: W1575 · W2000BLK · W2030BLK · W2050BLK · W3700BLK · W3700WHT · W4400 ·
五金油漆 12044118-028 · 12044118-087 · 12037001-028 · 12014107-028 · 12036001-028 ·
12051492-087 · W4590 · W9103 · 12070119-028 · 12070119-087 · 11289000 · 11292000)

Note: Blank Spaces are not permitted. If any item is not applicable, or no
information is available, the space must be marked to indicate that.

(As Used on Label and List)

Section I

Manufacturer's Name: Jidianbao Electrical Products (Shenzhen)Co.,Ltd.
Address (Number, Street City, State, and ZIP Code): (Region No. 117)Feng Huang Gang Village, Xin An, Baoan
County, Shenzhen City, Guangdong Province, China
Emergency Telephone Number: 0755-27938666
Telephone Number for Information: 0755-27938666
Date Prepared: 11-15-04
Signature of Preparer(optional): Andy Shum

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits	
			Recommended	%(optional)
Polyaromatic Hydrocarbons				0.003
Nonylphenol and ethoxylates				0.001
Hexavalent Chromium compounds				0.001-0.002

Section III – Physical/Chemical Characteristics

Boiling Point: 135°C
Vapor Pressure (mm Hg.):
Vapor Density (AIR = 1): 0.83
Solubility in Water: 1%
Appearance and Odor: Liquid, Fragrant Odor
Specific Gravity (H2O=1): 0.9
Melting Point: -87°C
Evaporation Rate:
(Butyl Acetate = 1)

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used): 210°C
Extinguishing Media: the fire extinguisher of CO2 or the other chemistry powder.
Special fire fighting Procedures: 1. The present worker bring the nearest fire extinguisher to extinguish fire.
2. The fire department of our company arrived the fire locale to extinguish fire.
3. Ask the fire company of the local government to helping.
Unusual Fire and Explosion Hazards: None
Flammable Limits: LEL: UEL:

Section V – Reactivity Data

Stability Unstable Conditions to Avoid
Stable
Incompatibility (Materials to Avoid):
Hazardous Decomposition or Byproducts:
Hazardous May Occur Conditions to Avoid: make fire far away.
Polymerization Will Not Occur

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.



