

Material Safety Data Sheet

U.S. Department of Labor

May be used to comply with

OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY <i>(As Used on Label and List)</i> Dri G745R1. Permanentmarkers. All G745 markers.	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
-------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------


Section I

Manufacturer's Name: Dri Mark Products Inc.	Emergency Telephone Number 1-516-484-6200
Address <i>(Number, Street, City, State, and ZIP Code)</i> 15 Harbor Park Dr.	Telephone Number for Information 1-516-484-6200
Pt. Washington, New York 11050	Date Prepared 1/22/09
	Signature of Preparer <i>(optional)</i>

Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% <i>(optional)</i>
N Propyl Alcohol	10-20	%		
Ethanol	40 -60	%		
Rosins	10 -15	%		
Spirit Dyes	20	%		
Housing	Non Reactive Plastic			
Nibs & Reservoirs	synthetic Fiber			

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.



Section III - Physical/Chemical Characteristics

Boiling Point	216 !	Specific Gravity (H ₂ O = 1)	> .85
Vapor Pressure (mm Hg.)	N/A	Melting Point	
Vapor Density (AIR = 1)	> 1	Evaporation Rate (Butyl Acetate = 1)	0.90
Solubility in Water: Soluble in water			
Appearance and Odor : Various colors/ alcoholic odor.			

Section IV - Fire and Explosion Hazard Data


Flash Point (Method Used): Unknown	Flammable Limits: Non-Flammable	LEL; N/A	UEL; N/A
Extinguishing Media: CO2, Water, Foam			
Special Fire Fighting Procedures: Standard fire fighting Equipment			
Unusual Fire and Explosion Hazards Non Flammable, None			

(Reproduce locally)

OSHA 174, Sept. 1985

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid: Avoid inhaling, swallowing,
	Stable:	X	
Incompatibility (<i>Materials to Avoid</i>) None			
Hazardous Decomposition or Byproducts None			
Hazardous Polymerization	May Occur		Conditions to Avoid: None
	Will Not Occur	X	



Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?: N/A	Skin?: N/A	Ingestion? : N/A
Health Hazards (<i>Acute and Chronic</i>) none			
Carcinogenicity: No known effects	NTP?: N/A	IARC Monographs?: N/A	OSHA Regulated?: No
Signs and Symptoms of Exposure: None, Since the ink is non volatile and soaked in a porous reservoir inside a non reactive vessel, there is no likelihood of over exposure.			
Medical Conditions none			
Emergency and First Aid Procedures Remove to fresh air, induce vomiting, call physician			

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: As the product is soaked in a porous reservoir. There is no possibility of spillage.
Waste Disposal Method: Dispose of in accordance with local government requirements .
Precautions to Be taken in Handling and Storing: Store in a cool dry area. Keep container tightly closed
Other Precautions:: Avoid contact with eyes.

--

Section VIII - Control Measures

Respiratory Protection (<i>Specify Type</i>) Avoid Inhalation, no additional protection required.		
Ventilation	Local Exhaust: No	Special: None
	Mechanical (<i>General</i>): No	Other: None
Protective Gloves: No	Eye Protection: Avoid contact with eyes	
Other Protective Clothing or Equipment: None		
Work/Hygienic Practices: Avoid contact with skin and eyes. Wash hands after use.		

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

