MATERIAL SAFETY DA	TA SHEET	CLOVE	R TECHNOLOG	IES CLOVER	TECHNOLOGIES	GROUP™
MAY BE USED TO COMPL	-		OLUMBUS STRE	Vote	MAGE IS EVER	YTHING"
HAZARD COMMUNICATION			VA, ILLINOIS 613		U	
29CRF 1910.1200	-		,			
	EMERGENCY	TELEPHONE	NUMBER 818-8	337-8100/800-394-9900		
				ER 818-837-8100		
DATE	PREPARED: 8/19/08			REPARER (OPTIONAL)		
SECTION 1 CHEMICAL						
Product/Chemical Name:	Canon 10	06 Toner				
CTG Product No: BC10	••••••					
CAS Number:	Mixture					
Other Designations:	N/A					
General Use:	Laser Printer					
SECTION 2 COMPOSIT	ION / INFORMATION	ON INGREDI	ENTS			
	CAS	EU		OSHA	ACGIH	OTHER
Ingredient Name:	NUMBER	NUMBER	%	PEL (TWA)	TLV	LIMITS
U				(9		
			Ton	er is regulated under OSHA a	as particulate not	
				otherwise regulate	•	
Styrene-Acrylate Copolymer	25767-47-9		40-60	not listed	not listed	
Iron Oxide	12227-89-3		35-55	10 mg/m3	5 mg/m3	
Organometallic complex			<5	not listed	not listed	
Amorphous Silica			<5	80/%SiO2 mg/m3	10 ma/m3	
				3.	5	
NDA = NO DATA AVAILAB N/A = NOT APPLICABLE	LE					
SECTION 3 HAZARDOU						IMIC
Primary Entry Routes:	Inhalation				NFPA/I	11115
Target Organs: N/A					HEALTH	
Acute Effects: N/A						4
Inhalation: Slight irritation			osure to large amo	unt of toner dust.		1
	use irritation by mechanic	al abrasion.			PPE (Sec.8)	-
Skin: Slight irritatio						
	unlikely route of entry und	er normal cond	itions of use.			
Carcinogenicity: N/A						
Medical Conditions Aggrav		posure:	Accumulation of du	st in the respiratory system		
-	cause congestion.					
the du		UISANCE PAR		rne particles (dust), it is recor ng to the American Conferen		ıt
SECTION 4 FIRST AID I		<u> </u>				
	resh air. Treat any irritatio	n symptomatics	ally. Call a physicia	n if condition persists		
Eye Contact: In case of co						
	Remove any contact lense					
Skin Contact: Wash well w						

 Ingestion:
 Clean mouth with water. Drink several glasses of water.

 After first aid, get appropriate in-plant paramedic or community medical support

if serious signs and symptoms persist.

Note to Physicians: N/A

Special Precautions / Procedures: N/A

SECTION 5 FIR		ASURES
Flash Point:	N/A	
Flash Point Metho	od: N/A	
Burning Rate:	N/A	
Auto Ignition Tem	perature: Not Det	ermined
LEL: N/A	١	
UEL: N/A	١	
Flammability Clas	sification: 1	Slight (HMIS, NFPA)
Extinguishing Me		pray, dry chemical, foam, carbon dioxide, or halon type extinguishers.
Unusual Fire of E		
Hazardous Comb	•	Carbon monoxide, carbon dioxide, nitrogen oxide and smoke.
		Under certain conditions some aliphatic aldehydes and carboxylic acids
		may form.
Fire Fighting Inct	untinna. Do not	•
		elease runoff from fire controls methods to sewers or waterways.
Fire-Fighting Equ	•	e fire may produce toxic thermal decomposition products, wear a
		tained breathing apparatus (SCBA) with full facepiece operated
		ure-demand or positive-pressure mode.
		EASE MEASURES
Spill / Leak Proce		
-		r for disposal, suction up remaining material with a high efficiency
vac	uum cleaner.	
Large Spills: Sco	oop into a containe	r for disposal, suction up remaining material with a high efficiency
vac	uum cleaner.	
Containment: For	large spills, avoid	suspending particles, collect for later disposal. Do not release
into	sewers or waterw	ays.
Cleanup: No	special requirement	nts.
Regulatory Requi		
SECTION 7 HAI		TORAGE
Handling Precauti	ons: Keep.co	ontainers closed at all times. Avoid creating dust. Keep away from ignition sources.
		ut of reach of children. Do not breath dust. Do not get in eyes or skin. Handle in ventilated area.
		to rough of official of the broat date. Do not get in by or of official handle in vortilated area.
Storage Requirem		a cool dry location. Keep away from excessive heat and sources of ignition
Storage Requirem Regulatory Regui	ents: Store in	a cool, dry location. Keep away from excessive heat and sources of ignition.
Regulatory Requi	rement: Store in N/A	
Regulatory Requi	rements: Store in rement: N/A	a cool, dry location. Keep away from excessive heat and sources of ignition. ROLS / PERSONAL PROTECTION
Regulatory Requi SECTION 8 EXF Engineering Cont	nents: Store in rement: N/A POSURE CONTR	ROLS / PERSONAL PROTECTION
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc	ROLS / PERSONAL PROTECTION
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel	eents: Store in rement: N/A POSURE CONTR rols: vide general or loc ow OSHA PELs (s	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s persion into the wo	ROLS / PERSONAL PROTECTION
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc bw OSHA PELs (s bersion into the wo ontrols:	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rrk area by controlling it at its source.
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis	eents: Store in rement: N/A POSURE CONTE rols: wide general or loc pw OSHA PELs (s persion into the wo ontrols: ction: Seek pr	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source.
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTE rols: wide general or loc pw OSHA PELs (s persion into the wo ontrols: ction: Seek pr	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rrk area by controlling it at its source.
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc bw OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source.
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s persion into the wo ontrols: ction: Seek pr Follow C a MSHA	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s persion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc tow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrout	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co	eents: Store in rement: N/A POSURE CONTI rols: vide general or loc bw OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rrk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTI rols: vide general or loc ow OSHA PELs (s persion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospl	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of a contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient heres</i> .
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTI rols: vide general or loc to WOSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi rg/Equipment: V	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient heres.</i> Wear chemically protective gloves, boots, aprons, and gauntlets to prevent
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTR rols: vide general or loc to OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospin pg/Equipment: V	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient heres.</i> Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: vide general or loc to WOSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospl g/Equipment: W	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel dis Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: wide general or loc to w OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: W	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> <i>heres.</i> Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro bel disp Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: wide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: V p c (2	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses.
Regulatory Requi SECTION 8 EXI Engineering Cont Ventilation: Pro bel disp Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: V p c (2 p Make emergen	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in co
Regulatory Requi SECTION 8 EXE Engineering Cont Ventilation: Pro bel disp Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTR rols: wide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: V p c (2 p Make emergen	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses.
Regulatory Requi SECTION 8 EXI Engineering Cont Ventilation: Pro bel disp Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTI rols: wide general or loc bw OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: V p Make emergen	ROLS / PERSONAL PROTECTION cal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant ork area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in conjunction with contact lenses. rotection must be worn instead of, or in co
Regulatory Requi SECTION 8 EXI Engineering Cont Ventilation: Pro bel disp Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTI rols: wide general or loc bw OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow (a MSHA to provid airborne nonrouti an SCB atmospi g/Equipment: V p Make emergen	ROLS / PERSONAL PROTECTION eal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant with a rea by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of a contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. toy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective
Regulatory Requi	eents: Store in rement: N/A POSURE CONTR rols: vide general or loc tow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospl og/Equipment: V p Make emergen uipment: Separat	ROLS / PERSONAL PROTECTION eal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant with a rea by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of a contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. <i>Warning! Air-purified respirators do not protect workers in oxygen-deficient</i> heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. toy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro- bel disj Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: vide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi og/Equipment: V p Make emergen uipment: Separat re-use. equipme ver eat, drink, or sr	ROLS / PERSONAL PROTECTION sal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. toy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective rentinated work streas. Practice good personal hygiene after using
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro- bel disj Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: vide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi og/Equipment: V p Make emergen uipment: Separat re-use. equipme ver eat, drink, or sr	ROLS / PERSONAL PROTECTION sal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant with a rea by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Wear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. usy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective every
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Pro- bel disj Administrative Co Respiratory Prote	eents: Store in rement: N/A POSURE CONTF rols: vide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi og/Equipment: V p Make emergen uipment: Separat re-use. equipme ver eat, drink, or sr	ROLS / PERSONAL PROTECTION sal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. toy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective rentinated work streas. Practice good personal hygiene after using
Regulatory Requi SECTION 8 EXF Engineering Cont Ventilation: Problem disp Administrative Co Respiratory Prote Protective Clothin Safety Stations: Contaminated Equ	eents: Store in rement: N/A POSURE CONTF rols: vide general or loc ow OSHA PELs (s bersion into the wo ontrols: ction: Seek pr Follow C a MSHA to provid airborne nonrouti an SCB atmospi og/Equipment: V p Make emergen uipment: Separat re-use. equipme ver eat, drink, or sr	ROLS / PERSONAL PROTECTION sal exhaust ventilation systems to maintain airborne concentrations ec.2). Local exhaust ventilation is preferred because it prevents contaminant rk area by controlling it at its source. ofessional advise prior to respirator selection and use. DSHA respirator regulations (29 CFR 1910.134) and, if necessary, wear VNIOSH-approved respirator. Select respirator based on its suitability de adequate worker protection for given working conditions, level of e contamination, and presence of sufficient oxygen. For emergency or ine operation (cleaning spills, reactor vessels, or storage tanks), wear A. Warning! Air-purified respirators do not protect workers in oxygen-deficient heres. Vear chemically protective gloves, boots, aprons, and gauntlets to prevent rolonged or repeated skin contact. Wear protective eyeglasses or hemical safety goggles, per OSHA eye and face protection regulations 29CFR 1910.133). Contact lenses are not eye protective devices. Appropriate rotection must be worn instead of, or in conjunction with contact lenses. toy eyewash stations and washing facilities available in work area. e contaminated work clothing from street clothes. Launder before Remove this material from your shoes and clean personal protective rentinated work streas. Practice good personal hygiene after using

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical State:		Water Solubility:	Negligible
Appearance and Odor:	Black, free flowing powder, odorless	Other Solubilities:	Partially soluble in toluene & tetrahydrofuran
Odor Threshold:	N/A	Boiling Point:	N/A
Vapor Pressure:	N/A	Freezing/Melting Point:	N/A
Vapor Density (Air=1):	Heavier than air.	Viscosity:	N/A
Formula Weight:	N/A	Refractive Index:	N/A
Density:	N/A	Surface Tension:	N/A
Specific Gravity:	(H ₂ O)=1, at 4°C): 1.5-2.5	% Volatile:	N/A
pH:	N/A	Evaporation Rate:	N/A

SECTION 10 STABILITY AND REACTIVITY

 Stability:
 Stable

 Polymerization:
 Will not occur

 Chemical Incompatibilities:
 None

 Conditions to Avoid:
 No Data

 Hazardous Decomposition Products:
 Only after combustion

SECTION 11 TOXICOLOGICAL INFORMATION

Eye Effects:	N/A	Toxicity Data:*	
Skin Effects:	N/A	Acute Inhalation Effects:	N/A
		Acute Oral Effects:	N/A
		Chronic Effects:	N/A
		Carcinogenicity:	N/A
		Mutagenicity: Ames Test	(Estimated from the results of
		Negative	testing the constituent components)
		Teratogenicity:	N/A

SECTION 12 ECO	OLOGICAL IN	NFORMATION			
Ecotoxicity:	N/A				
Environmental Fate	e: N/A				
Environmental Deg	radation:	N/A			
Soil Absorption / M	obility:	N/A			
SECTION 13 DIS	POSAL CON	SIDERATIONS			
Disposal: Wast	te material may	be incinerated / or recycled for	its Iron Oxide und	er conditions which meet	
all fe	deral, state, an	d local environmental regulation	IS.		
Disposal Regulator		•			
Disposal Regulator Container Cleaning	y Requiremen	ts: N/A			
	y Requiremen	ts: N/A			
Container Cleaning	y Requiremen and Disposal	ts: N/A : N/A	_		
Container Cleaning	y Requiremen and Disposal	ts: N/A : N/A FORMATION			
Container Cleaning	y Requiremen and Disposal	ts: N/A : N/A FORMATION			
Container Cleaning SECTION 14 TRA DOT Transportation	y Requiremen and Disposal	ts: N/A : N/A FORMATION	ly listed.	Quantity Lim	itations
Container Cleaning SECTION 14 TRA DOT Transportation Shipping Name:	ry Requiremen y and Disposal ANSPORT IN n Data (49 CFR	ts: N/A : N/A FORMATION R 172.101): Not specifical	ly listed.	Quantity Lim a) Passenger,	
Container Cleaning SECTION 14 TRA DOT Transportation Shipping Name: Shipping Symbol:	ry Requiremen y and Disposal ANSPORT IN n Data (49 CFR N/A	ts: N/A : N/A FORMATION R 172.101): Not specifical Packaging Authorizatio	ly listed. ons N/A	•	
Container Cleaning SECTION 14 TRA DOT Transportation Shipping Name: Shipping Symbol: Hazard Class:	ry Requiremen g and Disposal ANSPORT IN n Data (49 CFR N/A N/A	ts: N/A : N/A FORMATION R 172.101): Not specifical Packaging Authorization a) Exceptions:	ly listed. ons N/A	a) Passenger,	Aircraft, or
Container Cleaning SECTION 14 TRA DOT Transportation Shipping Name: Shipping Symbol: Hazard Class: ID No:	y Requiremen y and Disposal ANSPORT IN n Data (49 CFR N/A N/A N/A	ts: N/A : N/A FORMATION R 172.101): Not specifical Packaging Authorization a) Exceptions: b) Non-bulk Packaging:	ly listed. ons N/A N/A	a) Passenger, Railcar:	Aircraft, or
Disposal Regulator Container Cleaning SECTION 14 TRA DOT Transportation Shipping Name: Shipping Symbol: Hazard Class: ID No: Packing Group: Label:	y Requiremen y and Disposal ANSPORT IN n Data (49 CFR N/A N/A N/A N/A	ts: N/A : N/A FORMATION R 172.101): Not specifical Packaging Authorization a) Exceptions: b) Non-bulk Packaging:	ly listed. ons N/A N/A	a) Passenger, Railcar:	Aircraft, or N/A age Requirements

SECTION 15 REGULATORY INFORMATION

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification: (40 CFR 261): Not classified CERCLA Hazardous Substance (40 CFR 302.4) listed unlisted specific per RCRA, sec. 3001; CWA sec.311 (b)(4);

CWA, Sec. 307(a),CAA,Sec.112 CERCLA Reportable Quantity(RQ), Not listed

SARA 311/312 Codes: N/A

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Containment (29 CFR 1910.1000< Table Z-1-A): Particulates not otherwise regulated. **State Regulations:** Check your states regulations that may specifically list copy machine toner.

SECTION 16 OTHER INFORMATION

Prepared By: N/A Revision Notes: N/A Additional Hazard Rating System: N/A

> THIS INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY EXPRESS OR IMPLIED, REGARDLESS IT'S CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL, AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.