| | | | | | | | | 10 |
|-----------------|------------------|-------------------|---------------|---------------|-------------------|-----------------------------|---------------------------------------|-----------------|
| MATERIAL S | AFETY DA | TA SHEET | | CLOV | ER TECHNO | DLOGIES | CLOVER TECHN | NOLOGIES GROUP™ |
| MAY BE USED | TO COMPL | Y WITH OSHA | S | 4200 | COLUMBUS | STREET | YOUR IMAGE | IS EVERYTHING™ |
| HAZARD COM | MUNICATIO | N STANDARD | | OTTA | AWA, ILLINO | IS 61350 | C | |
| 29CRF 1910.12 | 200 | | | | | | | |
| | | | EMERG | ENCY TELE | EPHONE NU | MBER 1-800-356-272 | 8 | |
| | | | INFORM | IATION TEL | EPHONE NU | IMBER 1-919-774-380 |)8 | |
| | DATE | PREPARED: | 4/14/06 | | SIGNATURE | OF PREPARER (OPTIC | ONAL) | |
| SECTION 1 | CHEMICAL | PRODUCT / | NAME | | | | | |
| Product/Chem | ical Name: | | Toner fo | r use in HP | 1200 Printer | | | |
| CTG Product | No: BCS | 35 | | | | | | |
| CAS Number: | | Mixture | | | | | | |
| Other Designa | tions: | N/A | | | | | | |
| General Use: | | Laser Printer | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| SECTION 2 | COMPOSIT | | | | DIENTS | | | |
| | | | CAS | EU | % | OS | | I OTHER |
| Ingredient Nar | ne: | NU | MBER | NUMBER | 70 | PE | EL TLV | LIMITS |
| | | | | | | | | |
| | | | | | | Toner is regulated unc | | culate not |
| | - · | | | | | otherwi | se regulated: | |
| Styrene-Acrylat | te Copolymer | 6016 | 63-90-8 | | 40-65 | 00114 | | |
| | | | | | | | PEL: 15mg/m ³ | |
| Magnetite | | 130 | 9-37-1 | | 30-50 | 5mg/ | m ³ for respirable f | raction |
| | | | - - | | _ | | 3 | the state |
| Polypropylene | Wax | | 3-07-0 | | <5 | ACGIH TWA: 10mg/m | for nuisance par | ticulate |
| Dyestuff | | - | 4-55-3 | | <5 | | | |
| Silica | | 763 | 1-86-9 | | <1 | | | |
| | | | | | | | | |
| NDA = NO DA | | | | | | | | |
| N/A = NO DA | | LE | | | | | | |
| SECTION 3 | | | | | | | | |
| Primary Entry | | Inhalation | | | | | NE | PA/HMIS |
| Target Organs | | Initialation | | | | | HEALTH | 1 |
| Acute Effects: | | | | | | | FLMMBL | |
| Inhalation: | | on of respirator | / tract | | | | REACTIN | |
| Eye: | | use irritation by | | cal abrasion. | | | PPE (See | a \ |
| Skin: | Slight irritatio | - | | | | | , , , , , , , , , , , , , , , , , , , | , |
| Ingestion: | None known | | | | | | | |
| Carcinogenici | | | | | | | | |
| Medical Condi | • | vated By Long | -Term Ex | posure: | Accumulation | n of dust in the respirator | y system | |
| | | ause congestio | | | | | | |
| Chronic Effect | s: If the | se materials are | e used in a | manner that | could generate | e airborne particles (dust) | , it is recommende | ed that |
| | the du | ust may be trea | ted as a N | UISANCE PA | ARTICULATE a | ccording to the America | n Conference of G | overnment |
| | Indus | trial Hygienists | (ACGIH)(| TLV=10mg/m | ³). | | | |
| SECTION 4 | FIRST AID | MEASURES | | | | | | |
| Inhalation: | Remove to f | resh air. Treat a | any irritatio | on symptomat | ically. Call a ph | ysician if condition persi | sts. | |
| Eye Contact: | | | - | | | | | |
| | 15 minutes. | Remove any co | ontact lens | es to ensure | thorough flushi | ng. | | |
| Skin Contact: | Wash well w | ith soap and ru | nning wate | ər. | | | | |
| Ingestion: | N/A | | | | | | | |

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

| SECTION 5 | FIRE FIGHTING MEASURES |
|------------------|------------------------|

| SECTION 5 | FIRE FIGHT | ING MEASURES | |
|---|--|--|--|
| Flash Point: | N/A | | |
| Flash Point M | Method: N/A | | |
| Burning Rate | e: N/A | | |
| Auto Ignition | Temperature | Not Determined | |
| LEL: | N/A | | |
| UEL: | N/A | | |
| Flammability | Classification | : 1 Slight (HMIS | , NFPA) |
| Extinguishing | - | | nical, foam, carbon dioxide, or halon type extinguishers. |
| Unusual Fire | of Explosion | Hazards: May for | m flammable dust-air mixture. |
| Hazardous C | ombustion Pr | ducts: Carbon | monoxide, carbon dioxide, nitrogen oxide and smoke. |
| | | Under o | ertain conditions some aliphatic aldehydes and carboxylic acids |
| | | may for | m. |
| | | | from fire controls methods to sewers or waterways. |
| Fire-Fighting | Equipment: | | duce toxic thermal decomposition products, wear a |
| | | | g apparatus (SCBA) with full facepiece operated |
| | | | or positive-pressure mode. |
| | | L RELEASE MEAS | SURES |
| Spill / Leak P | | N/A | |
| Small Spills: | | | suction up remaining material with a high efficiency |
| | vacuum clea | | |
| Large Spills: | • | • | suction up remaining material with a high efficiency |
| | vacuum clea | | anti-day, and fairled an allowed Demoderate |
| Containment | • | | particles, collect for later disposal. Do not release |
| | into sewers of | • | |
| Cleanup: Bogulatory B | No special re | | |
| | Requirement: | | |
| | | AND STORAGE | |
| Handling Pre | | reep containers clos | ed at all times. Avoid creating dust. Keep away from ignition sources. |
| | | Store in a coal day 1- | |
| Storage Requestory R | | Store in a cool, dry lo | |
| Regulatory R | Requirement: | N/A | |
| Regulatory R SECTION 8 | Requirement: EXPOSURE | N/A | SONAL PROTECTION |
| Regulatory R SECTION 8 Engineering | Requirement: EXPOSURE Controls: | N/A CONTROLS / PER | SONAL PROTECTION |
| Regulatory R SECTION 8 | Equirement: EXPOSURE Controls: Provide gene | N/A CONTROLS / PER | SONAL PROTECTION |
| Regulatory R SECTION 8 Engineering | Exposure EXPOSURE Controls: Provide gene below OSHA | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e | SONAL PROTECTION Intilation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant |
| Regulatory R SECTION 8 Engineering (Venilation: | EXPOSURE EXPOSURE Controls: Provide gene below OSHA dispersion in | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e | SONAL PROTECTION |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e o the work area by co | SONAL PROTECTION entilation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. |
| Regulatory R SECTION 8 Engineering (Venilation: | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e o the work area by co Seek professional ad | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e o the work area by co Seek professional ad Follow OSHA respira | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-approximation | SONAL PROTECTION Intilation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local e o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appir to provide adequate of | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-apprise to provide adequate value of the provide adequate of the provid | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or |
| Regulatory R SECTION 8 Engineering Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-apprise to provide adequate va airborne contamination nonroutine operation | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant introlling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appl to provide adequate v airborne contaminatio nonroutine operation an SCBA. Warning! A | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: | N/A CONTROLS / PER ral or local exhaust ve PELs (sec.2). Local e o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appir to provide adequate v airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>hir-purified respirators do not protect workers in oxygen-deficient</i> |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by con- Seek professional ad Follow OSHA respira a MSHA/NIOSH-apput to provide adequate value airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. Sent: Wear chemical | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>hir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-apple to provide adequate variable airborne contamination onoroutine operation an SCBA. Warning! A atmosheres. ment: Wear chemica prolonged or response | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Illy protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appir to provide adequate ver airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. nent: Wear chemical prolonged or re- chemical safet | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations |
| Regulatory R SECTION 8 Engineering 0 Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appiration to provide adequate ver airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. thent: Wear chemical prolonged or re- chemical safett (29CFR 1910. | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant introlling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate |
| Regulatory R SECTION 8 Engineering Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Note: Controls: Protection: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appir to provide adequate v airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. hent: Wear chemical prolonged or re- chemical safett (29CFR 1910. protection mustices) | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Hy protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. |
| Regulatory R SECTION 8 Engineering Venilation: Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Nothing/Equipr | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-appir to provide adequate v airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. nent: Wear chemical prolonged or re chemical safet (29CFR 1910. protection must emergency eyewash s | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant introlling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Vir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. |
| Regulatory R SECTION 8 Engineering Venilation: Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Nothing/Equipr | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-apprito to provide adequate vant airborne contamination nonroutine operation an SCBA. Warning! A atmosheres. nent: Wear chemical prolonged or re chemical safet (29CFR 1910. protection musses Separate contamination | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant introlling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>hir-purified respirators do not protect workers in oxygen-deficient</i> Hy protective gloves, boots, aprons, and gauntlets to prevent appeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. ed wprk clothing from street clothes. Launder before |
| Regulatory R SECTION 8 Engineering Venilation: Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Nothing/Equipr | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by con- Seek professional ad Follow OSHA respira a MSHA/NIOSH-apple to provide adequate very airborne contamination onoroutine operation an SCBA. Warning! A atmosheres. Dent: Wear chemical prolonged or re- chemical safett (29CFR 1910. protection must emergency eyewash so Separate contamination | SONAL PROTECTION Initiation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant introlling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear roved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Vir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. |
| Regulatory R SECTION 8 Engineering Venilation: Administrativ Respiratory F Protective Cl Safety Station Contaminated | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Notection: Ins: Make d Equipment: | N/A CONTROLS / PER ral or local exhaust ver PELs (sec.2). Local er o the work area by co Seek professional ad Follow OSHA respira a MSHA/NIOSH-apple to provide adequate ver airborne contamination onoroutine operation an SCBA. Warning! A atmosheres. nent: Wear chemical prolonged or re- chemical safet (29CFR 1910. protection musical separate contamination re-use. Remove this in equipment. | SONAL PROTECTION Intilation systems to maintain airborne concentrations khaust ventilation is preferred because it prevents contaminant ntrolling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Hy protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. ed wprk clothing from street clothes. Launder before material from your shoes and clean personal protective |
| Regulatory R SECTION 8 Engineering Venilation: Venilation: Administrativ Respiratory F | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Nothing/Equipter Ins: Make d Equipment: Never eat, d | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by con- Seek professional ad Follow OSHA respira a MSHA/NIOSH-appertor to provide adequate very airborne contamination onnoutine operation an SCBA. Warning! A atmosheres. ment: Wear chemical prolonged or me chemical safett (29CFR 1910. protection must semergency eyewash as Separate contamination re-use. Remove this in equipment. nk, or smoke in works | SONAL PROTECTION Intilation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. ed wprk clothing from street clothes. Launder before material from your shoes and clean personal protective |
| Regulatory R SECTION 8 Engineering Venilation: Administrativ Respiratory F Protective Cl Safety Station Contaminated | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Noter eat, d | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by con- Seek professional ad Follow OSHA respira a MSHA/NIOSH-appertor to provide adequate very airborne contamination onnoutine operation an SCBA. Warning! A atmosheres. ment: Wear chemical prolonged or me chemical safett (29CFR 1910. protection must semergency eyewash as Separate contamination re-use. Remove this in equipment. nk, or smoke in works | SONAL PROTECTION Intilation systems to maintain airborne concentrations khaust ventilation is preferred because it prevents contaminant ntrolling it at its source. Vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability vorker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Hy protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. ed wprk clothing from street clothes. Launder before material from your shoes and clean personal protective |
| Regulatory R SECTION 8 Engineering Venilation: Administrativ Respiratory F Protective Cl Safety Station Contaminated | Requirement: EXPOSURE Controls: Provide gene below OSHA dispersion in ve Controls: Protection: Noter eat, d | N/A CONTROLS / PER ral or local exhaust very PELs (sec.2). Local ery o the work area by con- Seek professional ad Follow OSHA respira a MSHA/NIOSH-appertor to provide adequate very airborne contamination onnoutine operation an SCBA. Warning! A atmosheres. ment: Wear chemical prolonged or me chemical safett (29CFR 1910. protection must semergency eyewash as Separate contamination re-use. Remove this in equipment. nk, or smoke in works | SONAL PROTECTION Intilation systems to maintain airborne concentrations xhaust ventilation is preferred because it prevents contaminant ntrolling it at its source. vise prior to respirator selection and use. tor regulations (29 CFR 1910.134) and, if necessary, wear oved respirator. Select respirator based on its suitability worker protection for given working conditions, level of on, and presence of sufficient oxygen. For emergency or (cleaning spills, reactor vessels, or storage tanks), wear <i>Nir-purified respirators do not protect workers in oxygen-deficient</i> Ily protective gloves, boots, aprons, and gauntlets to prevent epeated skin contact. Wear protective eyeglasses or y goggles, per OSHA eye and face protection regulations 133). Contact lenses are not eye protective devices. Appropriate t be worn instead of, or in conjunction with contact lenses. stations and washing facilities available in work area. ed wprk clothing from street clothes. Launder before material from your shoes and clean personal protective |

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

| Physical State: | | Water Solubility: | Negligible |
|------------------------|--|-------------------------|------------|
| Appearance and Odor: | Black, free flowing powder, faint odor | Other Solubilities: | N/A |
| Odor Threshold: | N/A | Boiling Point: | N/A |
| Vapor Pressure: | N/A | Freezing/Melting Point: | N/A |
| Vapor Density (Air=1): | Heavier than air. | Viscosity: | N/A |
| Formula Weight: | N/A | Refractive Index: | N/A |
| Density: | N/A | Surface Tension: | N/A |
| Specific Gravity: | (H ₂ O)=1, at 4°C): 1.3-1.8 | % Volatile: | N/A |
| pH: | N/A | Evaporation Rate: | N/A |

SECTION 10 STABILITY AND REACTIVITY

Stability: N/A Polymerization: N/A Chemical Incompatibilities: N/A Conditions to Avoid: Avoid open flames Hazardous Decomposition Products: Toxic decomposition products formed on combustion

SECTION 11 TOXICOLOGICAL INFORMATION MISCELLANEOUS TOXICOLOGICAL INFORMATION

In a Xerox sponsored chronic inhalation study in rats using a special toner, there were no lung changes at all in the lowest exposure level (1 mg/cu. M) the most relevant level to potential human exposure. A very slight degree of fibrosis was noted in 25% of the animals at midexposure level (4 mg/cu. m) in all animals. These findings are attributed to "Lung Overload". A generic response to excessive amounts of any dust retained in the lungs for a prolonged interval. The special test toner was ten times more respirable than commercially available toners to comply with EPA testing protocol and would not function properly in a copier of printing equipment.

Mutagenicity: No Mutagenicity detected by AMES test.

Carcinogens: None Present

This material when used as intended, does not present a health or safety hazard.

SECTION 12 ECOLOGICAL INFORMATION

Ecotoxicity: N/A Environmental Fate: N/A Environmental Degradation: N/A Soil Absorption / Mobility: N/A

SECTION 13 DISPOSAL CONSIDERATIONS

Disposal: Waste material may be incinerated / or recycled for its Iron Oxide under conditions which meet all federal, state, and local environmental regulations.

Disposal Regulartory Requirements: N/A

Container Cleaning and Disposal: N/A

SECTION 14 TRANSPORT INFORMATION

| Shipping Name: | N/A | Packaging Authorization | ons | Quantity Limitations |
|---------------------|-----|-------------------------|-----|-----------------------------|
| Shipping Symbol: | N/A | a) Exceptions: | N/A | a) Passenger, Aircraft, or |
| Hazard Class: | N/A | b) Non-bulk Packaging: | N/A | Railcar: N/A |
| ID No: | N/A | c) Bulk Packaging: | N/A | |
| Packing Group: | N/A | | | Vessel Stowage Requirements |
| Label: | N/A | | | a) Vessel Stowage: N/A |
| Special Provisions: | N/A | | | b) Other: N/A |

SECTION 15 REGULATORY INFORMATION

EPA Regulations:

RCRA Hazardous Waste Number: Not listed (40 CFR 261.33) RCRA Hazardous Waste Classification: (40 CFR 261): Not classified CERCLA Hazardous Substance (40 CFR 302.4) listed unlisted specific per RCRA, sec. 3001; CWA sec.311 (b)(4);

CWA, Sec. 307(a),CAA,Sec.112 CERCLA Reportable Quantity(RQ), Not listed

SARA 311/312 Codes: N/A

SARA Toxic Chemical (40 CFR 372.65): Not listed

SARA EHS (Extremely Hazardous Substance) (40CFR 355): Not listed, Threshold Planning Quantity (TPQ)

OSHA Regulations:

Air Containment (29 CFR 1910.1000< Table Z-1-A): Particulates not otherwise regulated.

State Regulations: Check your states regulations that may specifically list copy machine toner.

SECTION 16 OTHER INFORMATION

Prepared By: N/A Revision Notes: N/A Additional Hazard Rating System: N/A

> THIS INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY EXPRESS OR IMPLIED, REGARDLESS IT'S CORRECTNESS. THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL, AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH THE HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

