

**Lifetime Repair Corporation**  
**3985 Eastern Rd**  
**Norton, Oh 44203**  
**Telephone: 330-706-9791**

## **Material Safety Data Sheet**

### **1. PRODUCT IDENTIFICATION**

**Product Name:** FIX – A - CHIP  
**Item No:** LTR-105  
**Product Type:** SEALANT

### **2. COMPOSITION/INFORMATION ON INGREDIENTS**

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
Water 7732-18-5	30-40	NOT LISTED	NOT LISTED
VINYL ACETATE POLYMERS 108-05-4	20-30	10 ppm TWA; 35 mg/m3 TWA	10 ppm TWA; 30 mg/m3 TWA

Nonylphenol , branched, ethoxylated 68412-54-4	0.1-1.0	NOT LISTED	NOT LISTED
Cristobalite 14464-46-1	.1-1.0	.025 mg/m3	0.05 mg/m3
Nepheline syenite 37244-96-5	10-20	NOT LISTED	NOT LISTED
Acrylic resin Sup.conf	10-20	NOT LISTED	NOT LISTED

### **3. HAZARDS IDENTIFICATION**

**Toxicity:** Causes respiratory irritation. When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor

concentrations below the OSHA permissible limit for formaldehyde.

**Primary Routes of Entry:** Eye and skin contact, ingestion, inhalation.

**Signs and Symptoms of Exposure:** Overexposure may cause nasal irritation.

**Medical Conditions Recognized as**

**Being Aggravated by Exposure:**

**None known**

### **4. FIRST AID MEASURES**

**Ingestion:** If swallowed, DO NOT induce vomiting. Obtain medical attention immediately.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapors. Oxygen or artificial respiration if needed.

Obtain medical attention.

**Skin Contact:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## **5. FIRE FIGHTING MEASURES**

**Flash Point (°F/C):** None

**Recommended Extinguishing Media:** None - does not burn.

**Special Fire-Fighting Procedures:** No special procedures.

**Hazardous Products Formed by Fire or Thermal**

**Decomposition:** Formaldehyde, Oxides of carbon.

**Unusual Fire/Explosion Hazards:** None

**Lower Explosive Limit:** Not determined.

**Upper Explosive Limit:** Not determined.

## **6. ACCIDENTAL RELEASE MEASURES**

**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Clean up spills thoroughly as residue is slippery.

## **7. HANDLING AND STORAGE**

**Storage:** Keep from freezing

**Handling:** spilled substance increases risk of slipping

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Eyes:** Safety glasses.

**Skin:** Rubber or plastic gloves

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** colored liquid

**Odor:** weak

**Boiling Point (°F):** Greater than 100°c ( 212 °F)

**pH:** 4.5

**Solubility in Water:** SOLUBLE

**Specific Gravity:** 1.07

**VOC Content (Wt. %):** Not determined

**Vapor Pressure:** 18.5 mm Hg

**Vapor Density (Air=1):** Not Determined

**Evaporation Rate:** Not Determined

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** STABLE

**Hazardous Polymerization:** WILL NOT OCCUR

**Incompatibilities:** None known

**Conditions to Avoid:** None anticipated

**Hazardous Products Formed by Fire or Thermal**

**Decomposition:** if stored properly none at increased temperature: acetic acid

## **11. TOXICOLOGICAL INFORMATION**

**See Section 3**

## **12. ECOLOGICAL INFORMATION**

Not readily biodegradable

## **13. DISPOSAL CONSIDERATIONS**

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.

US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

## **14. TRANSPORTATION INFORMATION**

**DOT (49CFR 172)**

**Domestic Ground Transport**

**DOT Shipping Name:** Unrestricted

**Hazard Class:** NONE

**UN/ID Number:** None

**Marine Pollutant:** None

### **IATA**

**Proper Shipping Name:** not regulated

**Class or Division:** None

**UN/NA Number:** None

### **IMDG**

**Proper Shipping:** Unrestricted

**Hazard Class:** None

**UN Number:** None

## **15. REGULATORY INFORMATION**

**SARA 313 Chemicals:** The following component(s) is listed as a SARA Section 313 Toxic Chemical.

**SARA 313 Information**

VINYL ACETATE

**CALIFORNIA PROP 65:**

**WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

**TSCA Inventory Status:**

**Listed on Inventory: YES**, All components of this product are listed (or exempt) on the EPA TSCA inventory.

**16. OTHER INFORMATION**

**Estimated NFPA Rating:**

HEALTH 1, FLAMMABILITY 0 , REACTIVITY 0

**Estimated HMIS Classification:**

HEALTH 1, FLAMMABILITY 0, PHYSICAL

HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Revision Date: March/01/2008

Company: Lifetime Repair Corporation

3985 Eastern Rd

Norton, Oh 44203

Telephone: 330-706-9791

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

