Gillette Medical Evaluation Laboratories

56801 56901

5700/ 57/0/ 57/0/

401 Professional Drive Gaithersburg, MD 20879 Tel 301.590.9781

Page I of 4

GMEL#

1391

# MATERIAL SAFETY DATA SHEET

Evaporation ( Butyl Acetate =1) (by volume >1	°F por De	Molecular Weight: Synonyms:  Ing Point NA °C  Pensity (air=1)  3.4		Freezing °F essure @ 83		°C			
Methylcyclohexane (108-87-2) Titanium Dioxide (13463-67-7) Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s) Mustard Oil (57-06-7) Masking Fragrance  B. — PHYSICAL DATA  Boiling Point  -212 °F ~100 °C NA  Specific Gravity (H <sub>2</sub> O=1) Val  -1.3  Evaporation (Butyl Acetate =1) (by volume)  >1  % Volatiles	Metti °F por De	Molecular Weight: Synonyms:  Ing Point NA °C  Pensity (air=1)  3.4	NA Colored C	Freezing °F essure @ 83	Point NA 100				
Methylcyclohexane (108-87-2) Titanium Dioxide (13463-67-7) Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s) Mustard Oil (57-06-7) Masking Fragrance  B. — PHYSICAL DATA  Boiting Point —212 °F ~100 °C NA  Specific Gravity (H <sub>2</sub> O=1) Val —1.3  Evaporation (Butyl Acetate =1) (by volume) —>1  % Volatiles S —40  Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s) Flammable Limits in Air (% by volume)  C. — REACTIVITY Stability Stable unstate Conditions to Avoid Product is flammable. Avoid contact with open or other ignition sources.  incompatible Materials	Metti °F por De	ng Point NA °C ensity (air=1) 3.4	NA Vapor Pr	Freezing °F essure @ 83	Point NA 100				
Titanium Dioxide (13463-67-7) Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s) Mustard Oil (57-06-7) Masking Fragrance  Boiling Point -212 °F ~100 °C NA  Specific Gravity (H <sub>2</sub> O=1) Val -1.3  Evaporation (Butyl Acetate =1) (by volume) >1  % Volatiles ~40  Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s) 25°F (Closed Cup) for product Flammable Limits in Air (% by volume)  C.— REACTIVITY  Stability Stable unstate Conditions to Avoid Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	°F por De	ng Point NA °C ensity (air=1) 3.4	NA Vapor Pr	Freezing °F essure @ 83	Point NA 100				
Mineral Spirits (64742-48-9) Resin, Dispersant, Colorant(s) Mustard Oil (57-06-7) Masking Fragrance  B. — PHYSICAL DATA  Boiling Point —212 °F ~100 °C NA  Specific Gravity (H <sub>2</sub> O=1) Val —1.3  Evaporation (Butyl Acetate =1) (by volume)  >1  % Volatiles S —40  Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s) 25°F (Closed Cup) for product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	°F por De	ng Point NA °C ensity (air=1) 3.4 etion in Air	NA Vapor Pr	Freezing °F essure @ 83	Point NA 100				
Boiling Point  -212 °F ~100 °C NA  Specific Gravity (H <sub>2</sub> O=1) Val  -1.3  Evaporation (Butyl Acetate =1) (by volume)  >1  % Volatiles S  -40  Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s) 25°F (Closed Cup) for product fluids in Air (% by volume)  C.— REAGTIVITY  Stability Stable unstate Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	°F por De	NA °C ensity (air=1) 3.4 elion in Air	Vapor Pr	°F essure @ 83	NA 100				
Specific Gravity (H <sub>2</sub> O=1) Value 1.3  Evaporation (Butyl Acetate =1) (by volume >1  % Volatiles Support	°F por De	NA °C ensity (air=1) 3.4 elion in Air	Vapor Pr	°F essure @ 83	NA 100				
Specific Gravity (H <sub>2</sub> O=1) Value 1.3  Evaporation (Butyl Acetate =1) (by volume >1  % Volatiles Support	por De	ensity (air=1)  3.4 ation in Air	Vapor Pr	essure @ 83	100				
Evaporation ( Butyl Acetate =1) (by volume >1  % Volatiles		3.4 ation in Air		83		°F			
Evaporation ( Butyl Acetate =1) (by volume >1		ation in Air	A	<del></del>	mm Hg				
Butyl Acetate =1)   (by volume   >1	<b>5</b> -4		A			_			
(by volume    Solution   Solution	こさいいだ	ô			remperature				
% Volatiles	@ _	°F)		°F .		°C			
Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s) 25°F (Closed Cup) for product Flammable Limits in Air (% by volume) Lower  C.—REACTIVITY  Stability Stable unstate  Conditions to Avoid Product is flammable. Avoid contact with open or other ignition sources.	NA		NA NA						
Appearance/Odor Colored fluid with a pungent Flash Point and Test Method(s)  Flammable Limits in Air (% by volume)  C.— REACTIVITY  Stability  Stabile  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials		ity in Water		_4.	D.T.A				
Flash Point and Test Method(s)  Flammable Limits in Air (% by volume)  C.—REACTIVITY  Stability  Stabile  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.	Neg	gligible		<b>р</b> Н	NA				
Test Method(s)  Flammable Limits in Air (% by volume)  C.—REACTIVITY  Stability  Stable  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	solv	ent odor							
C.— REACTIVITY  Stability Stable unstate  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	ct								
C. — REACTIVITY  Stability Stable unstate  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials		• • •			7 %				
Stability Stable unstable  Conditions to Avoid  Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials		1.2 %	Uppe	r <u>6</u> .		_			
Conditions to Avoid Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials									
Product is flammable. Avoid contact with open or other ignition sources.  Incompatible Materials	)le	Polymerization		y occur	will n	ot occu			
or other ignition sources.			Condition	s to Avoid					
Incompatible Materials		ic NA							
·	flam								
Strong oxidizers	flam			nposition Pr					
	flam		rdous Decor	Thermal degradation may produce oxides of carbon and nitrogen and various hydrocarbons.					
* IF MULTIPLE INGREDIENTS, INCLUDE CA  Enotrotes  Physical data, except Specific Gravity and % Ve	flam	Thermal degrad	ation may p	oroduce o ydrocarbo	ns.				

Page 2 of 4

#### D. -- HEALTH HAZARD DATA

Occupational Exposure Limits PEL's, TLV's, etc.)

8-Hour TWA's: Methylcyclohexane - 400 ppm (ACGIH)

Titanium Dioxide - 10 mg/cu m (OSHA/ACGIH)

Mineral Spirits - 300 ppm (Manufacturer recommendation)

These levels are not anticipated under foreseeable use conditions.

Warning Signals

NA

Routes/Effects of Exposure

No adverse effects anticipated from normal use. If vapors are deliberately concentrated and 1. Inhalation

inhaled (abuse), the following symptoms may occur: respiratory irritation, dizziness,

drowsiness, headache, nausea, unconsciousness, convulsions, cardiac sensitization, coma and

death. (Mustard oil is added to the product as an abuse deterrent.)

No adverse effects anticipated from normal use. Depending on amount ingested, most of the 2. Ingestion

> symptoms described above may occur. Estimated LD<sub>so</sub> in rats is greater than 5 ml/kg or between 1 pint and 1 quart in humans (ref. Gosselin, Smith and Hodge, Clinical Toxicology of

Commercial Products, 5th Ed., 1984). Aspiration may result in chemical pneumonitis.

3. Skin a. Contact

No adverse effects anticipated from normal use. Irritation may occur if contact is

prolonged/repeated.

b. Absorption

No adverse effects anticipated from normal use. Solvent can be absorbed through skin

(prolonged contact), but not likely in acutely toxic amounts.

4. Eye Contact If splashed into eye, irritation can occur.

5. Other NA

#### E. — ENVIRONMENTAL IMPACT

1. Applicable Regulations

2. DOT Hazard Class -ORM-D

3. DOT Shipping Name -Consumer Commodity

Environmental Effects

All components of this product comply with the U.S. Toxic Substances Control Act (TSCA).

**GMEL#** 

1391

Page 3 of 4

F. EXPOSURE CONTROL METHODS		
Engineering Controls		
None under normal use conditions.		}
Eye Protection		
None under normal use conditions.		
Skin Protection None under normal use conditions.		
None under normal use conditions.		
		İ
Respiratory Protection		
None under normal use conditions.		
		ļ
		İ
Other		
Product is non-hazardous when used as directed in an office/room with normal air circula	tion.	
G WORK PRACTICES		
Handling and Storage		
Product is flammable. No unusual handling or storage when used as directed; when store	d in large q	uantities
(as in warehouse), it should be in a well-ventilated, cool area, away from ignition sources		'
Normal Clean Up		<del></del>
Pick up spills with towels, tissues, etc.		
Waste Disposal Methods		
Dispose in accordance with applicable federal, state and local laws.		
	GMEL#	1391

Page 4 of 4

### H. — EMERGENCY PROCEDURES

Steps to be taken if material is released to the environment or spilled in the work area Not applicable

Fire and Explosion Hazard

Product is flammable. May produce hazardous decomposition products.

Extinguishing Media

Dry chemical, foam, carbon

dioxide.

Firefighting Procedures

In fires involving large quantities of product, use self-contained breathing apparatus. Cool fire-exposed containers with water fog/spray.

## I. -- FIRST AID AND MEDICAL EMERGENCY PROCEDURES

Eyes

Flush with plenty of water. If irritation persists, obtain medical attention.

Skin

Wash with soap and water.

Inhalation

No adverse effects anticipated from normal use. In an abuse situation, remove from source of exposure. Treat symptomatically. Oxygen may be administered. Seek medical attention immediately and refer to "Notes to Physician" below.

Ingestion

Consult physician.

Notes to Physician

Contains methylcyclohexane and mineral spirits which, if aspirated, may cause chemical pneumonitis. The inhalation of concentrated vapors may produce cardiac sensitization, contraindicating the use of sympathomimetic agents.

Replaces #1197, Sections A, D revised.

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

MSDS-4 (8/95)

GMEL#

1391