G-2

Material Safety Data Sheet			U.S. Department of Labor									
May be used to comply with			Occupational Safety and Health Administration(Non-									
OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements. IDENTITY (As used on Label and list) -			Mandatory Form) Form Approved OMB No. 1218-0072 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space									
							G2, G2 Pro & G2 M	G25//R	must be marked to indicate that.			
							(G25/7, G67, BDGL7					
							Black, Blue, Red, Green, Burgundy	Purple, Pink, Turq	uoise and			
SECTION I		,										
Manufacturer's Name	Τe	Telephone Number										
PILOT Corporation	81	!-3-3538-3700										
Address(Number, Street, C	City State & Zip)	Fa	ax Number									
2-6-21, Kyobashi, Chuoki		1-3-3538-3909										
m 1			ate Prepared									
Tokyo, 104-8304 Japa	an		ugust 21, 2007									
			Prepared by									
			. Fukasawa									
Section II - Hazardo												
Hazardous Compo	nents(Specific Chem	nical Identity;Com	mon Name(s))	OSHA PEI	L ACGIH Other Limits % TLV Recommended (optional							
NAME	CAS. NO.	TLV(PPM)	WT. (%)		COMPONENT							
Ethylene Glycol	107-21-1	<i>N.A.</i>	20.0		INK							
Triethanolamine	102-71-6		5.0									
Section III - Physical	/Chemical Char	racteristics										
	/Chemical Char	acteristics	N	.A.	Specific Gravity N.A (H20=1)							
		racteristics		A.	Melting Point N.A							
Section III - Physical Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i>	N.D.	racteristics	N		Melting Point N.A Evaporation Rate (Butyl Acetate							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i>	N.D.	racteristics	N	7. A	Melting Point N.A Evaporation Rate							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i>	N.D. D.		N	7. A	Melting Point N.A Evaporation Rate (Butyl Acetate							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i>	N.D. D. iting instrument,	, No Smell	N	7. A	Melting Point N.A Evaporation Rate (Butyl Acetate							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and	N.D. D. iting instrument, Explosion Haza	, <i>No Smell</i> ard Data	N	7. A	Melting Point N.A Evaporation Rate (Butyl Acetate							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used)	N.D. D. iting instrument, Explosion Haza	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used)	N.D. iting instrument, Explosion Haza N.D. ase of fire, use w	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>In o</i> Special Fire Fighting Proc	N.D. iting instrument, Explosion Haza N.D. ease of fire, use wedures N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>In C</i>	N.D. iting instrument, Explosion Haza N.D. ease of fire, use wedures N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>In o</i> Special Fire Fighting Proc	N.D. iting instrument, Explosion Haza N.D. ease of fire, use wedures N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point N.D. Vapor Pressure(mm Hg) Vapor Density(Air=1) N. Solubility in Water N.D. Appearance and Odor Wr Section IV - Fire and Flash Point(Method Used) Extinguishing Media In Company of the Special Fire Fighting Procedutes and N.D. Autoignition Temp. N.D.	N.D. iting instrument, Explosion Haza N.D. ease of fire, use wedures N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point <i>N.D.</i> Vapor Pressure(mm Hg) Vapor Density(Air=1) <i>N.</i> Solubility in Water <i>N.D.</i> Appearance and Odor <i>Wr</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>In a</i> Special Fire Fighting Procedures and N.D.	N.D. iting instrument, Explosion Haza N.D. ease of fire, use we dures N.A. on Hazards N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	V.A	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							
Boiling Point N.D. Vapor Pressure(mm Hg) Vapor Density(Air=1) N. Solubility in Water N.D. Appearance and Odor Wr Section IV - Fire and Flash Point(Method Used) Extinguishing Media In C Special Fire Fighting Proc Autoignition Temp. N.D. Unusual Fire and Explosion	N.D. iting instrument, Explosion Haza N.D. ease of fire, use we dures N.A. on Hazards N.A.	, <i>No Smell</i> a rd Data Flammabl	N N N N N N N N N N N N N N N N N N N	l powder	Melting Point N.A Evaporation Rate (Butyl Acetate = 1) LELN.D. UELN.D.							

Page 1 of 3

G-2

Incompatibility	N.A.	1	
(Materials to Avoid) Hazardous Decomposition	N.A.	+	
or Byproducts			
Hazardous Polymerization	May Occur		Condition to Avoid
	May Not Occur	X	None
Section VI - Health Ha	zard Data		
Route(s) of Entry: <i>None</i>	Inhalation? <i>N.A</i> .	Skin? Yes (Ink)	Ingestion? Yes (Ink)
Health Hazards(Acute and C	hronic) N.D.		
Signs and Symptoms of Expo	oorro N D		
Signs and Symptoms of Expe	osure IV.D.		
Medical Conditions	N D		
Generally Aggravated by Ex	posure IV.D.		
		* 77 1 1/1	* 10 10 100
		-	plenty of water, consult medical Skin:
Wash with soap & wate	r Ingestion: Drink mui	k ana consuit meaic	eal.
Section VII - Precaution			
Steps to Be Taken in Case M	•		
Flush with water, soak	up with absorbent mo	aterials	
Waste Disposal			
In accordance with Nat	ional, State and Loca	al regulations.	
Precautions to Be Taken in H	landling and Storing		
None			
Other Precautions			
None			
Section VIII - Control	Maggirag		
Respiratory Protection(Speci			
Ventilation		st <i>Not Required</i>	Special <i>Not Required</i>
Ventuation		General) <i>Not Required</i>	Other Not Required
Protective Gloves	#1200mms	Eye Protection	Other 1400 recycle of
Rubber or polyethyrene glov	ves	Goggles.	
Other Protective Clothing or Not Required			
Work/Hygienic Practices			
After handling, wash hands	well with soan and water		

Page 2 of 3

Return to Data Sheet Index

RETURN TO DATA SHEET INDEX

