

SECTION 1:  
MANUFACTURER

MATERIAL SAFETY DATA SHEET  
SPECIALTY INK CO., INC.  
20 DUNTON AVENUE  
DEER PARK, NY 11729  
PHONE NUMBER 516-586-3666  
EMERGENCY PHONE 1-800-688-4005  
FAX NUMBER 516-586-3874

PAGE 1

I-009

INK NAME: 5127 INK - *offi + Uni*

DATE PREPARED  
04/01/99

HEALTH: 1 CODE: 0=MINIMAL  
FLAMMABILITY: 1 1=SLIGHT  
REACTIVITY: 0 2=MODERATE  
PERSONAL PROTECTION: B 3=SERIOUS  
4=SEVERE

*Judy  
Rush  
Sales  
Vic SV*

SECTION 2: HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	ACGIH-TLV	OSHA-PEL	CAS NO
DIETHYLENE GLYCOL	6.00	1000 PPM	1000 PPM	111-46-6
ETHYLENE GLYCOL*	25.00	50 PPM	50 PPM	107-21-1

THIS CHEMICAL IS SUBJECT TO THE REPORTING REQUIRMENTS OF  
SARA TITLE III, SECTION 313 OF THE EMERGENCY PLANNING AND  
COMMUNITY RIGHT TO KNOW ACT OF 1986 AND OF 40 CFR 372  
THIS PRODUCT IS IN COMPLIANCE WITH THE EPA TSCA INVENTORY.

SECTION 3: PHYSICAL & CHEMICAL CHARACTERISTICS

BOILING POINT: 212 F  
MELTING POINT: 32 F  
VAPOR DENSITY: 4.15  
SPECIFIC GRAVITY: 1.0211  
REACTIVITY IN WATER: NONE  
SOLUBILITY IN WATER: COMPLETE  
AUTO IGNITION: 444 F  
VAPOR PRESSURE: <1 MM HG  
APPEARANCE & ODOR: MOBILE LIQUID, NO ODOR  
APPEARANCE & ODOR: VOC: 21.83 GMS/L  
LEL/UEL %: 1.7 15.3  
FLASH POINT: 232 F  
METHOD: CLOSED CUP

**RECEIVED**  
OCT 26 1999  
BY PURCHASING

SECTION 4: FIRE & EXPLOSION DATA

EXTINGUISHING MEDIA: WATERSPRAY  
EXTINGUISHING MEDIA: CARBON DIOXIDE  
EXTINGUISHING MEDIA: DRY CHEMICAL  
EXTINGUISHING MEDIA: ALCOHOL RESISTANT FOAM  
EXTINGUISHING MEDIA: WATER IN INK WILL STOP FIRE AFTER FLASH  
SPECIAL FIRE PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS  
SPECIAL FIRE PROCEDURES: WEAR PROTECTIVE CLOTHING AND EQUIPMENT  
SPECIAL FIRE PROCEDURES: USE WATERSPRAY TO COOL FIRE-EXPOSED AREA  
SPECIAL FIRE PROCEDURES: USE WATERSPRAY TO PROTECT PERSONNEL  
UNUSUAL HAZARDS: WATER ON FIRE MAY CAUSE FROTHING  
UNUSUAL HAZARDS: FIRE SHOULD GO OUT DUE TO WATER IN INK

OfficeWorld.com does not independently verify, and accordingly does not warrant, the accuracy of any information contained in this MSDS.

