Material Safety Data Sheet

xerox

MSDS No.: A-1020 **Issue Date:** 5/2/05

Revision Date: 12/14/09 **Telephone Number(s):** Safety Information: (800) 828-6571

Health Emergency: (585) 422-2177

Transportation Emergency (Chemtrec): (800) 424-9300

Section 1: Product Identification

Xerox Corporation, Office Group

Wilsonville, OR 97070-1000

Trade Name/Synonyms: Phaser 6300/Phaser 6350/

Phaser 6360 Toner

Part No.: 106R1073, 106R1074, 106R1075, 106R1076, 106R1082, 106R1083,106R1084, 106R1085, 106R1086,106R1087, 106R1088, 106R1089,106R1144, 106R1145, 106R1146, 106R1147, 106R1214, 106R1215,106R1216, 106R1217, 106R1218,106R1219, 106R1220, 106R1221,106R1222, 106R1223, 106R1224,106R1225, 016-2104-00, 016-2105-00, 016-2106-00, 016-2107-00, 097S03375

WHMIS Status: This is not a WHMIS controlled product

> **Ingredients (% by wt.)** CAS No. Polyester resins (80-90%) Proprietary Pigments (4-10%) 1333-86-4 Carbon black Cyan 147-14-8 Magenta **Proprietary**

Proprietary Yellow Wax (3-5%) **Proprietary** Additives (0.5-5%) **Proprietary**

Section 2: Emergency and First Aid

Primary Route of Entry:

Inhalation Eyes:

Flush with water

Manufacturer:

P.O. Box 1000

Wash with soap and water

Inhalation:

Remove from exposure.

Ingestion

Dilute stomach contents with several glasses of milk or water

Symptoms of Overexposure:

Minimal respiratory tract irritation may occur as with exposure to large amounts of any non-toxic dust.

Medical Conditions Generally Aggravated by Exposure:

None when used as described by product literature.

Additional Information

None

Section 3: Toxicology and Health Information

The toxicity data noted below is based on the test results of similar reprographic materials:

Oral LD₅₀: >5 g/kg (rats) practically non-toxic. TLV: 10 mg/m³ (inhalable particles) Dermal LD₅₀: >5 g/kg (rabbits) practically non-toxic 3 mg/m³ (respirable particles)

Inhalation LC₅₀: >5 mg/l (rats, 4hr exposure) practically non-toxic. PEL: 15 mg/m³ (total dust)

>20 mg/l (calculated 1 hr exposure) non-poisonous, DOT 5 mg/m³ (respirable dust)

STEL: Not established Not an irritant

Eye Irritation: Ceiling: **Skin Sensitization:** Not a sensitizer Not established XEL^1 : **Skin Irritation:** Not an irritant 2.5 mg/m³ (total dust) **Human Patch:** Non-irritating, non-sensitizing

0.4 mg/m³ (respirable dust)

Mutagenicity: No mutagenicity detected in Ames assay.

Carcinogens: None present

Aquatic LC₅₀: >1000 mg/l (fathead minnows) non-toxic.

Additional Information: The results obtained from a Xerox sponsored Chronic Toner Inhalation Study demonstrated no lung change in rats for the lowest (1mg/m3) exposure level (the level most relevant to potential human exposure). A very slight degree of fibrosis was noted in 25% of animals at the middle (4mg/m³) exposure level, while a slight degree of fibrosis was noted in all the animals at the highest (16 mg/m³) exposure level. These findings are attributed to "lung overloading", a generic response to excessive amounts of any dust retained in the lungs for prolonged period. This study was conducted using a special test toner to comply with EPA testing protocol. The test toner was ten times more respirable than commercially available Xerox toner, and would not be functionally suitable for Xerox equipment.

¹XEL-Xerox Exposure Limit

Trade Name: Phaser 6300/Phaser 6350/ Phaser 6360 Toner



MSDS No.: A-1020

Section 4 - Physical Data

Appearance/Odor: Fine black, magenta, yellow, cyan powder/ **Softening Range:** 120°F -140°F

faint odor

Boiling Point:Not applicableMelting Point:N.D.Solubility in Water:NegligibleSpecific Gravity $(\mathbf{H_2O=1})$ ~ 1

Evaporation Rate: Not applicable **Vapor Pressure (mm Hg):** Not applicable

Vapor Density (Air=1) Not applicable **pH: Volatile:** Not applicable % (Wt.) Not applicable % (Vol.)

Section 5 – Fire and Explosion Data

Flash Point (Method Used): Not applicable

Flammable Limits: LEL: Not applicable, UEL: Not applicable

NFPA 704: Consumer Use and Storage ("Cartridge"/ "Bottle") – Health -0, Fire-1, Reactivity-0

Manufacturing Use and Storage ("Bulk Containers") – Health -0, Fire-3, Reactivity-0

Extinguishing Media: Avoid direct stream –gently apply water mist, water fog, or foam

Special Fire Fighting Procedures: Avoid inhalation of smoke. Wear protective clothing and self-contained breathing

apparatus.

Fire and Explosion Hazards: Toner is a combustible powder. Like most organic materials in powder form, it can

form explosive mixtures when dispersed in air.

Section 6 – Reactivity Data

Stability: Stable

Hazardous Polymerization: Will Not Occur

Hazardous Decomposition Products: Products of combustion may be toxic. Avoid breathing smoke.

Incompatibility (Materials to Avoid): None known

Section 7 – Special Protection Information

Respiratory Protection:None required when used as intended in Xerox equipment.
Protective Gloves:
None required when used as intended in Xerox equipment.
None required when used as intended in Xerox equipment.

Other: For use other than normal customer –operating procedures (such as in bulk toner

processing facilities), goggles and respirators may be required. For more information,

contact Xerox.

Section 8 – Special Precautions

Handling and Storage: Keep container tightly closed

Conditions to Avoid: Avoid prolonged inhalation of excessive dust.

Section 9 – Spill, Leak, and Disposal Procedures

For Spills or Leakage: Sweep up or vacuum spilled toner and carefully transfer into sealable waster container.

Sweep slowly to minimize generation of dust during clean-up. If vacuum is used, the motor must be rated as *dust tight*. A conductive hose bonded to the machine should be used to reduce static buildup (See Section 5). Residue can be removed with soap and cold water. Garments may be washed or dry-cleaned, after removal of loose toner.

Waste Disposal Method: This material is not a hazardous waste according to Federal Regulation 40 CFR 261

when disposed. State and Local requirements may, however, be more restrictive. Consult with the appropriate State and Local waste disposal authorities for additional

information. Incinerate only in a closed container.

Section 10 – Transportation Information

This product is not regulated as a hazardous material