

877-816-8767



A Omni Smart Digital UPS System With features like reliable battery backup, AVR, surge suppression, line noise filtering, an LCD screen and a USB port, these UPS Systems offer complete power protection solutions for PCs, A/V components and all home and office electronics. A large, rotatable, illuminated LCD screen with dimmer switch alerts you to potential power problems and automatic voltage regulation corrects brownouts without using battery power. USB ports work with free unattended shutdown software, so your files are saved in the case of a blackout, even when you are not there. \$200,000 Ultimate Lifetime Insurance. Manufacturer's three-year warranty.

ID No.	VA	Outlets	Run Time*	Joules	Dimensions	Unit	Price
1 TRP-OMNI900LCD* *	900 VA	4 UPS/Surge; 4 Surge Only	50 minutes	870 J	3½" × 6½" × 12"	EA	207.00

* UL1778; CSA; FCC Part 15 Class B; RoHS. Run Time based on single PC load with 15" flat panel monitor.



B Digital Smart UPS System Digital Smart UPS Systems' reliable battery backup keeps PC systems operational for up to 90 minutes during blackouts. Automatic voltage regulation (AVR) corrects brownouts back to safe 120V power without draining the UPS battery. Surge suppression and EMI/RFI line noise filtering prevent hardware damage and poor audio and video performance. A large, rotatable, illuminated LCD screen with dimmer switch shows incoming power conditions and UPS operations in real time. Dateline surge protection. USB ports work with free unattended shutdown software, so your files are saved in the case of a blackout, even when you're not there. \$250,000 Ultimate Lifetime Insurance. Manufacturer's three-year warranty.

ID No.	VA	Outlets	Run Time*	Joules	Dimensions	Unit	Price
2 TRP-SMART1000LCD* *	1000 VA	4 Surge Only; 4 UPS/Surge	60 minutes	1038 J	3¾" × 7½" × 12"	EA	228.00
3 TRP-SMART1500LDT* *	1500 VA	5 UPS/5 Surge Only	10 minutes	650 J	5¾" × 15¼" × 8"	EA	298.00

* UL1778; CSA; NOM; FCC Part 15 Class B; FCC Part 68; RoHS. Run Time based on single PC load with 15" flat panel monitor.



C SmartPro® Rackmount UPS System Ideal protection for all rackmount equipment. Advanced automatic voltage regulation corrects brownouts and overvoltages without using battery. USB & DB9 communication ports and included software for complete power management. Built-in LCD screen displays operating conditions. \$250,000 Ultimate Lifetime Insurance. Manufacturer's limited two-year standard warranty; three with registration.

ID No.	VA	Outlets	Half Load Run	Joules	Dimensions	Unit	Price
4 TRP-SMART1500RM2* *	1500 VA	8 UPS/2 Surge	13 minutes	570 J	17½" × 19" × 3½"	EA	939.00
5 TRP-SMART2200RMX* *	2200 VA	8 UPS/2 Surge	12 minutes	570 J	17½" × 19" × 3½"	EA	1,449.00
6 TRP-SMART3000RM2* *	3000 VA	9 UPS/Surge	11 minutes	570 J	17½" × 19" × 3½"	EA	1,632.00

* CSA; FCC Part 15 Class A; NOM; UL1778.



D SmartRack™ Premium Enclosure Secure, organized storage for all EIA-310-compliant 19" rackmount equipment. Toolless keyhole mounting speeds up PDU installation and cable management. Models feature adjustable mounting rails and easy-view depth index, locking and reversible front and split rear doors and locking, removable split side panels. Compliant with the latest Payment Card Industry (PCI) security standards. Three-thousand pound capacity. Manufacturer's five-year warranty.

ID No.	Units	Enclosure/Rack Style	W × D × H	Shpg. Wt.	Unit	Price
7 TRP-SR25UB* *	25U	4-Post	23¾" × 43" × 49"	218 lbs.	EA	1,575.00
8 TRP-SR42UB* *	42U	4-Post	22 ¾" × 43" × 78½"	328 lbs.	EA	1,704.00

* RoHS Compliant.



E Wall Mount SmartRack Enclosure Ideal for secure, high-density networking environments. Designed for easy integration of accessories. Indexed, adjustable mounting rails. Vendor-neutral square hole/cage nut mounting. Fully compatible with hot-aisle/cold aisle configurations. Ideal storage solution for standard rackmount equipment with limited floor space. Sturdy wall mounting bracket and steel frame can accommodate up to 140 lbs. of equipment. Adjustable vertical mounting rails accommodate rack equipment. Removable side panels, reversible front door and cable routing ports on top and bottom panels. Fully assembled. Compliant with the latest Payment Card Industry (PCI) security standards. Manufacturer's five-year warranty.

ID No.	Units	Enclosure/Rack Style	W × D × H	Shpg. Wt.	Unit	Price
9 TRP-SRW6U* *	6U	Wall-Mount	23½" × 17½" × 14½"	32 lbs.	EA	270.00
10 TRP-SRW12US* *	12U	Wall-Mount	23½" × 21½" × 25"	64 lbs.	EA	558.00

* RoHS Compliant.

Convenient air conditioner cools "hot spots"



Self-Contained Portable 120V Air Conditioning Unit Use for supplemental cooling for confined areas or "hot spots" that your HVAC system can't reach. Designed for quick, simple installation—plugs into a standard 5-15R outlet with no adapter required. 12,000 BTU, 3.4KW, 120V, 60Hz. Manufacturer's limited one-year warranty.

ID No.	W × D × H	Shpg. Wt.	Unit	Price
11 TRP-SRCOOL12K* *	12¾" × 19¾" × 32¾"	68 lbs.	EA	1,098.00

* RoHS Compliant.



1500

[A GUIDE TO OUR ICONS]

See page two for more information

Call if You Don't See
What You NeedContains At Least 10%
Total Recycled ContentGreener
Choices

p1499

p1501